

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
25 314938	C 18-15-17	7	2	6.5	8	APC E	4.1 x 4.1	2891	68%	14,058	4.14	112
		7	2	6.5	8	APC E	4.5 x 4.1	2891	68%	12,623	5.02	129
		7	2	6.5	8	APC E	4.7 x 4.25	2891	68%	12,074	5.36	133
25 314939	C 18-15-25	10.5	3	4	5	APC E	4.1 x 4.1	2011	73%	14,784	3.04	124
		7	2	4	5	APC E	4.1 x 4.1	2053	67%	11,139	1.76	70
		7	2	4	5	APC E	4.5 x 4.1	2053	67%	10,082	2.24	81
		7	2	4	5	APC E	4.75 x 4.75	2053	67%	8,854	2.79	73
		7	2	4	5	APC E	4.75 x 5.5	2053	67%	8,711	2.85	65
		7	2	4	5	APC E	5.25 x 4.75	2053	67%	7,843	3.24	92
		7	2	4	5	APC E	5.25 x 6.25	2053	67%	7,273	3.5	75
		7	2	4	5	APC E	5.5 x 4.5	2053	67%	8,299	3.04	88
		7	2	4	5	APC E	5.5 x 6.25	2053	67%	7,273	3.5	66
		7	2	4	5	APC E	6 x 4	2053	67%	8,141	3.11	128
		7	2	4	5	Aeronaut E	6 x 5	2053	67%	7,142	3.56	106
		7	2	4	5	APC E	6 x 5.5	2053	67%	6,952	3.64	103
		7	2	4	5	Aeronaut E	6.5 x 4	2053	67%	7,289	3.49	144
		7	2	4	5	APC E	4.75 x 4.5	2053	67%	9,205	2.63	67
		7	2	4	5	APC E	5 x 5	2053	67%	8,418	2.98	72
7	2	4	5	APC E	5.1 x 4.5	2053	67%	7,750	3.28	103		
7	2	4	5	APC E	4.7 x 4.25	2053	67%	9,713	2.4	86		
25 314940	C 18-20-10	7	2	7	10	APC E	4.5 x 4.1	2387	69%	13,263	4.8	143
		7	2	7	10	APC E	4.75 x 4.75	2387	69%	11,973	6.41	135
		7	2	7	10	APC E	4.75 x 5.5	2387	69%	11,765	6.67	123
		7	2	7	10	APC E	4.75 x 4.5	2387	69%	12,387	5.89	130
		7	2	7	10	APC E	5 x 5	2387	69%	11,547	6.94	135

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		7	2	7	10	APC E	4.7 x 4.25	2387	69%	12,902	5.25	151
		7	2	6.5	8	APC E	4.5 x 4.1	2120	69%	11,815	3.38	112
		7	2	6.5	8	APC E	4.75 x 4.75	2120	69%	10,639	4.47	106
		7	2	6.5	8	APC E	4.75 x 5.5	2120	69%	10,467	4.63	96
		7	2	6.5	8	APC E	5.25 x 4.75	2120	69%	9,496	5.52	134
		7	2	6.5	8	APC E	5.25 x 6.25	2120	69%	9,022	5.96	115
		7	2	6.5	8	APC E	5.5 x 4.5	2120	69%	10,042	5.02	134
		7	2	6.5	8	APC E	5.5 x 6.25	2120	69%	9,022	5.96	102
		7	2	6.5	8	APC E	6 x 4	2120	69%	9,944	5.11	196
		7	2	6.5	8	Aeronaut E	6 x 5	2120	69%	8,904	6.07	170
		7	2	6.5	8	APC E	6 x 5.5	2120	69%	8,680	6.27	166
		7	2	6.5	8	Aeronaut E	6.5 x 4	2120	69%	9,062	5.92	227
		7	2	6.5	8	APC E	4.75 x 4.5	2120	69%	11,003	4.13	100
		7	2	6.5	8	APC E	5 x 5	2120	69%	10,232	4.84	106
		7	2	6.5	8	APC E	5.1 x 4.5	2120	69%	9,519	5.5	158
		7	2	6.5	8	APC E	4.7 x 4.25	2120	69%	11,480	3.69	120
25 314942	C 18-20-16	10.5	3	5.5	7	APC E	4.5 x 4.1	1665	75%	14,000	3.45	160
		10.5	3	5.5	7	APC E	4.7 x 4.25	1665	75%	13,619	3.77	169
		7	2	5.5	7	APC E	4.75 x 4.75	1664	72%	9,311	2.67	81
		7	2	5.5	7	APC E	4.75 x 5.5	1664	72%	9,215	2.76	74
		7	2	5.5	7	APC E	5.25 x 4.75	1664	72%	8,590	3.38	110
		7	2	5.5	7	APC E	5.25 x 6.25	1664	72%	8,205	3.76	95
		7	2	5.5	7	APC E	5.5 x 4.5	1664	72%	8,937	3.04	103
		7	2	5.5	7	APC E	5.5 x 6.25	1664	72%	8,205	3.76	84
		7	2	5.5	7	APC E	6 x 4	1664	72%	8,846	3.13	153

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		7	2	5.5	7	Aeronaut E	6 x 5	1664	72%	8,113	3.85	139
		7	2	5.5	7	APC E	6 x 5.5	1664	72%	7,954	4.01	138
		7	2	5.5	7	Aeronaut E	6.5 x 4	1664	72%	8,227	3.74	185
		7	2	5.5	7	APC E	7 x 5	1664	72%	6,950	5	213
		7	2	5.5	7	APC E	4.75 x 4.5	1664	72%	9,529	2.45	72
		7	2	5.5	7	APC E	5 x 5	1664	72%	9,035	2.94	83
		7	2	5.5	7	APC E	5.1 x 4.5	1664	72%	8,561	3.41	127
		7	2	9	19	APC E	4.1 x 4.1	3593	73%	17,739	8.61	181
25 314943	C 22-14-25	7	2	7.5	9	APC E	4.1 x 4.1	2778	70%	15,362	5.06	135
		7	2	7.5	9	APC E	4.5 x 4.1	2778	70%	14,211	6.34	165
		7	2	7.5	9	APC E	4.7 x 4.25	2778	70%	13,719	6.89	171
25 314944	C22-14-31	7	2	4.5	7	APC E	4.1 x 4.1	2209	72%	12,897	2.68	94
		7	2	4.5	7	APC E	4.5 x 4.1	2209	72%	11,992	3.49	116
		7	2	4.5	7	APC E	4.75 x 4.5	2209	72%	11,130	4.25	102
		7	2	4.5	7	APC E	4.7 x 4.25	2209	72%	11,634	3.8	123
25 314945	C 22-16-18	7	2	10	13	APC E	4.1 x 4.1	2579	71%	15,291	4.75	133
		7	2	10	13	APC E	4.5 x 4.1	2579	71%	14,350	6.04	168
		7	2	10	13	APC E	4.75 x 4.75	2579	71%	12,868	8.06	156
		7	2	10	13	APC E	4.75 x 5.5	2579	71%	12,618	8.41	143
		7	2	10	13	APC E	5.5 x 4.5	2579	71%	12,083	9.14	204
		7	2	10	13	APC E	6 x 4	2579	71%	12,038	9.2	294
		7	2	10	13	APC E	4.75 x 4.5	2579	71%	13,349	7.41	154
		7	2	10	13	APC E	5 x 5	2579	71%	12,400	8.7	156
		7	2	10	13	APC E	4.7 x 4.25	2579	71%	13,936	6.6	177
25 314946	C 22-16-25	10.5	3	7	11	APC E	4.1 x 4.1	1692	70%	15,230	3.12	132

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		10.5	3	7	11	APC E	4.5 x 4.1	1692	70%	14,391	4.02	169
		10.5	3	7	11	APC E	4.75 x 4.5	1692	70%	13,480	4.99	157
		10.5	3	7	11	APC E	4.7 x 4.25	1692	70%	14,016	4.42	179
		7	2	7	11	APC E	4.75 x 4.75	1711	69%	9,591	3.07	86
		7	2	7	11	APC E	4.75 x 5.5	1711	69%	9,490	3.19	78
		7	2	7	11	APC E	5.25 x 4.75	1711	69%	8,846	3.95	117
		7	2	7	11	APC E	5.25 x 6.25	1711	69%	8,470	4.39	102
		7	2	7	11	APC E	5.5 x 4.5	1711	69%	9,208	3.52	111
		7	2	7	11	APC E	5.5 x 6.25	1711	69%	8,470	4.39	90
		7	2	7	11	APC E	6 x 4	1711	69%	9,122	3.62	163
		7	2	7	11	Aeronaut E	6 x 5	1711	69%	8,378	4.5	149
		7	2	7	11	APC E	6 x 5.5	1711	69%	8,215	4.69	147
		7	2	7	11	Aeronaut E	6.5 x 4	1711	69%	8,495	4.36	198
		7	2	7	11	APC E	7 x 5	1711	69%	7,191	5.9	229
		7	2	7	11	Aeronaut E	7 x 7	1711	69%	6,497	6.71	167
		7	2	7	11	APC E	8 x 4	1711	69%	6,451	6.77	267
		7	2	7	11	Aeronaut E	8.5 x 5	1711	69%	6,491	6.72	263
		7	2	7	11	APC E	4.75 x 4.5	1711	69%	9,814	2.81	77
		7	2	7	11	APC E	5 x 5	1711	69%	9,315	3.4	88
		7	2	7	11	APC E	5.1 x 4.5	1711	69%	8,831	3.96	135
		7	2	7	11	APC E	4.7 x 4.25	1711	69%	10,106	2.46	93
		7	2	7	11	APC E	7 x 6	1711	69%	6,322	6.92	198
		7	2	11	15	APC E	4.75 x 4.75	2365	69%	13,554	8.7	173
		7	2	11	15	APC E	4.75 x 5.5	2365	69%	13,367	9.16	161
		7	2	11	15	APC E	5.5 x 4.5	2365	69%	12,968	10.16	239

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		7	2	11	15	APC E	6 x 4	2365	69%	12,955	10.19	343
		7	2	11	15	APC E	4.75 x 4.5	2365	69%	13,891	7.86	168
		7	2	11	15	APC E	5 x 5	2365	69%	13,225	9.52	178
25 314948	C 22-20-15	7	2	10	12	APC E	5.25 x 4.75	1824	70%	10,387	6.23	161
		7	2	10	12	APC E	5.25 x 6.25	1824	70%	10,118	6.85	145
		7	2	10	12	APC E	5.5 x 4.5	1824	70%	10,744	5.41	156
		7	2	10	12	APC E	5.5 x 6.25	1824	70%	10,118	6.85	130
		7	2	10	12	APC E	6 x 4	1824	70%	10,700	5.52	229
		7	2	10	12	Aeronaut E	6 x 5	1824	70%	10,046	7.01	220
		7	2	10	12	APC E	6 x 5.5	1824	70%	9,885	7.38	218
		7	2	10	12	Aeronaut E	6.5 x 4	1824	70%	10,152	6.77	287
		7	2	10	12	APC E	7 x 5	1824	70%	8,902	9.63	363
		7	2	10	12	APC E	5.1 x 4.5	1824	70%	10,437	6.12	191
		10.5	3	10	12	APC E	4.7 x 4.25	1803	72%	16,278	6.53	241
25 314949	C 22-20-20	7	2	8	10	APC E	5.25 x 4.75	1438	76%	8,574	3.03	109
		7	2	8	10	APC E	5.25 x 6.25	1438	76%	8,329	3.48	98
		7	2	8	10	APC E	5.5 x 4.5	1438	76%	8,784	2.64	100
		7	2	8	10	APC E	5.5 x 6.25	1438	76%	8,329	3.48	87
		7	2	8	10	APC E	6 x 4	1438	76%	8,728	2.75	149
		7	2	8	10	Aeronaut E	6 x 5	1438	76%	8,270	3.59	145
		7	2	8	10	APC E	6 x 5.5	1438	76%	8,163	3.79	145
		7	2	8	10	Aeronaut E	6.5 x 4	1438	76%	8,344	3.45	191
		7	2	8	10	APC E	7 x 5	1438	76%	7,440	5.12	247
		7	2	8	10	Aeronaut E	7 x 7	1438	76%	6,897	6.11	188
		7	2	8	10	APC E	8 x 4	1438	76%	6,841	6.22	301

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		7	2	8	10	APC E	8 x 6	1438	76%	5,925	7.9	264
		7	2	8	10	Aeronaut E	8.5 x 5	1438	76%	6,893	6.12	296
		7	2	8	10	Aeronaut E	8.5 x 6	1438	76%	6,317	7.18	285
		7	2	8	10	APC E	9 x 4.5	1438	76%	6,191	7.41	363
		7	2	8	10	APC E	5.1 x 4.5	1438	76%	8,556	3.06	127
		7	2	8	10	APC E	7 x 6	1438	76%	6,755	6.38	226
		10.5	3	8	10	APC E	4.75 x 4.75	1435	77%	12,759	4.31	153
		10.5	3	8	10	APC E	4.75 x 5.5	1435	77%	12,611	4.56	143
		10.5	3	8	10	APC E	5.5 x 4.5	1435	77%	12,280	5.1	211
		10.5	3	8	10	APC E	6 x 4	1435	77%	12,255	5.14	305
		10.5	3	8	10	APC E	4.75 x 4.5	1435	77%	13,030	3.87	146
		10.5	3	8	10	APC E	5 x 5	1435	77%	12,480	4.77	158
25 314910	C 24-33-10	7	2	17	27	APC E	4.1 x 4.1	4025	74%	22,574	16.76	296
25 314950	C 28-22-25	10.5	3	8.5	13	APC E	4.75 x 4.75	1408	74%	12,230	3.95	141
		10.5	3	8.5	13	APC E	4.75 x 5.5	1408	74%	12,083	4.15	130
		10.5	3	8.5	13	APC E	5.25 x 4.75	1408	74%	11,236	5.27	188
		10.5	3	8.5	13	APC E	5.25 x 6.25	1408	74%	10,926	5.68	169
		10.5	3	8.5	13	APC E	5.5 x 4.5	1408	74%	11,743	4.6	191
		10.5	3	8.5	13	APC E	5.5 x 6.25	1408	74%	10,926	5.68	152
		10.5	3	8.5	13	APC E	6 x 4	1408	74%	11,706	4.65	277
		10.5	3	8.5	13	Aeronaut E	6 x 5	1408	74%	10,840	5.79	258
		10.5	3	8.5	13	APC E	6 x 5.5	1408	74%	10,627	6.07	255
		10.5	3	8.5	13	Aeronaut E	6.5 x 4	1408	74%	10,978	5.61	338
		10.5	3	8.5	13	APC E	7 x 5	1408	74%	9,403	7.69	408
		10.5	3	8.5	13	APC E	5 x 5	1408	74%	11,937	4.34	145

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		10.5	3	8.5	13	APC E	<b>5.1 x 4.5</b>	1408	74%	11,345	5.12	227
		14	4	8.5	13	APC E	<b>4.5 x 4.1</b>	1390	75%	16,533	4.24	225
		14	4	8.5	13	APC E	<b>4.75 x 4.75</b>	1390	75%	15,207	5.94	218
		14	4	8.5	13	APC E	<b>4.75 x 5.5</b>	1390	75%	14,941	6.29	204
		14	4	8.5	13	APC E	<b>5.5 x 4.5</b>	1390	75%	14,421	6.96	303
		14	4	8.5	13	APC E	<b>6 x 4</b>	1390	75%	14,446	6.92	432
		14	4	8.5	13	APC E	<b>4.75 x 4.5</b>	1390	75%	15,668	5.35	221
		14	4	8.5	13	APC E	<b>5 x 5</b>	1390	75%	14,798	6.47	223
		14	4	8.5	13	APC E	<b>4.7 x 4.25</b>	1390	75%	16,181	4.69	238
		7	2	8.5	13	APC E	<b>5.25 x 4.75</b>	1405	70%	8,208	2.85	100
		7	2	8.5	13	APC E	<b>5.25 x 6.25</b>	1405	70%	7,937	3.25	89
		7	2	8.5	13	APC E	<b>5.5 x 6.25</b>	1405	70%	7,937	3.25	79
		7	2	8.5	13	Aeronaut E	<b>6 x 5</b>	1405	70%	7,872	3.35	131
		7	2	8.5	13	APC E	<b>6 x 5.5</b>	1405	70%	7,762	3.52	131
		7	2	8.5	13	Aeronaut E	<b>6.5 x 4</b>	1405	70%	7,950	3.23	173
		7	2	8.5	13	APC E	<b>7 x 5</b>	1405	70%	7,016	4.63	218
		7	2	8.5	13	Aeronaut E	<b>7 x 7</b>	1405	70%	6,469	5.45	165
		7	2	8.5	13	APC E	<b>8 x 4</b>	1405	70%	6,433	5.5	265
		7	2	8.5	13	APC E	<b>8 x 6</b>	1405	70%	5,533	6.85	227
		7	2	8.5	13	APC E	<b>8 x 8</b>	1405	70%	5,011	7.63	205
		7	2	8.5	13	Aeronaut E	<b>8.5 x 5</b>	1405	70%	6,465	5.45	261
		7	2	8.5	13	Aeronaut E	<b>8.5 x 6</b>	1405	70%	5,894	6.31	248
		7	2	8.5	13	Aeronaut E	<b>8.5 x 7</b>	1405	70%	5,358	7.11	236
		7	2	8.5	13	APC E	<b>9 x 4.5</b>	1405	70%	5,792	6.46	315
		7	2	8.5	13	Aeronaut E	<b>9.5 x 5</b>	1405	70%	5,183	7.37	318

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		7	2	8.5	13	Aeronaut E	<b>9.5 x 6</b>	1405	70%	5,085	7.52	279
		7	2	8.5	13	Aeronaut E	<b>9.5 x 7</b>	1405	70%	4,697	8.1	269
		7	2	8.5	13	APC E	<b>10 x 5</b>	1405	70%	5,057	7.56	339
		7	2	8.5	13	Aeronaut E	<b>10 x 6</b>	1405	70%	4,756	8.01	309
		7	2	8.5	13	Aeronaut E	<b>9 x 5</b>	1405	70%	4,946	7.73	304
		7	2	8.5	13	APC E	<b>9 x 6</b>	1405	70%	5,085	7.52	301
		7	2	8.5	13	APC E	<b>5.1 x 4.5</b>	1405	70%	8,177	2.9	115
		7	2	8.5	13	APC E	<b>7 x 6</b>	1405	70%	6,327	5.66	198
<b>25 314951</b>	<b>C 28-22-27</b>	10.5	3	7.5	11	APC E	<b>4.75 x 4.75</b>	1316	75%	11,501	3.24	124
		10.5	3	7.5	11	APC E	<b>4.75 x 5.5</b>	1316	75%	11,371	3.39	115
		10.5	3	7.5	11	APC E	<b>5.25 x 4.75</b>	1316	75%	10,603	4.3	167
		10.5	3	7.5	11	APC E	<b>5.25 x 6.25</b>	1316	75%	10,283	4.68	150
		10.5	3	7.5	11	APC E	<b>5.5 x 4.5</b>	1316	75%	11,058	3.76	167
		10.5	3	7.5	11	APC E	<b>5.5 x 6.25</b>	1316	75%	10,283	4.68	134
		10.5	3	7.5	11	APC E	<b>6 x 4</b>	1316	75%	11,008	3.82	243
		10.5	3	7.5	11	Aeronaut E	<b>6 x 5</b>	1316	75%	10,198	4.78	227
		10.5	3	7.5	11	APC E	<b>6 x 5.5</b>	1316	75%	10,003	5.01	224
		10.5	3	7.5	11	Aeronaut E	<b>6.5 x 4</b>	1316	75%	10,327	4.63	298
		10.5	3	7.5	11	APC E	<b>7 x 5</b>	1316	75%	8,854	6.37	359
		10.5	3	7.5	11	Aeronaut E	<b>7 x 7</b>	1316	75%	8,047	7.32	258
		10.5	3	7.5	11	APC E	<b>8 x 4</b>	1316	75%	7,897	7.5	407
		10.5	3	7.5	11	Aeronaut E	<b>8.5 x 5</b>	1316	75%	8,040	7.33	403
		10.5	3	7.5	11	APC E	<b>5 x 5</b>	1316	75%	11,222	3.57	128
		10.5	3	7.5	11	APC E	<b>5.1 x 4.5</b>	1316	75%	10,676	4.21	200
		14	4	7.5	11	APC E	<b>4.5 x 4.1</b>	1300	75%	15,551	3.5	199



JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		14	4	7.5	11	APC E	<b>4.75 x 4.75</b>	1300	75%	14,364	4.9	194
		14	4	7.5	11	APC E	<b>4.75 x 5.5</b>	1300	75%	14,133	5.17	182
		14	4	7.5	11	APC E	<b>5.5 x 4.5</b>	1300	75%	13,663	5.73	268
		14	4	7.5	11	APC E	<b>6 x 4</b>	1300	75%	13,666	5.72	384
		14	4	7.5	11	APC E	<b>4.75 x 4.5</b>	1300	75%	14,773	4.41	193
		14	4	7.5	11	APC E	<b>5 x 5</b>	1300	75%	13,985	5.35	199
		14	4	7.5	11	APC E	<b>5.1 x 4.5</b>	1300	75%	13,167	6.31	310
		14	4	7.5	11	APC E	<b>4.7 x 4.25</b>	1300	75%	15,236	3.87	211
		7	2	7.5	11	APC E	<b>5.25 x 6.25</b>	1306	68%	7,413	2.71	78
		7	2	7.5	11	APC E	<b>5.5 x 6.25</b>	1306	68%	7,413	2.71	68
		7	2	7.5	11	Aeronaut E	<b>6 x 5</b>	1306	68%	7,351	2.79	113
		7	2	7.5	11	APC E	<b>6 x 5.5</b>	1306	68%	7,255	2.93	113
		7	2	7.5	11	Aeronaut E	<b>6.5 x 4</b>	1306	68%	7,422	2.7	149
		7	2	7.5	11	APC E	<b>7 x 5</b>	1306	68%	6,579	3.85	189
		7	2	7.5	11	Aeronaut E	<b>7 x 7</b>	1306	68%	6,081	4.53	146
		7	2	7.5	11	APC E	<b>8 x 4</b>	1306	68%	6,066	4.56	234
		7	2	7.5	11	APC E	<b>8 x 6</b>	1306	68%	5,238	5.69	201
		7	2	7.5	11	APC E	<b>8 x 8</b>	1306	68%	4,753	6.35	183
		7	2	7.5	11	Aeronaut E	<b>8.5 x 5</b>	1306	68%	6,077	4.54	230
		7	2	7.5	11	Aeronaut E	<b>8.5 x 6</b>	1306	68%	5,553	5.26	220
		7	2	7.5	11	Aeronaut E	<b>8.5 x 7</b>	1306	68%	5,058	5.94	210
		7	2	7.5	11	APC E	<b>9 x 4.5</b>	1306	68%	5,477	5.36	279
		7	2	7.5	11	APC E	<b>9 x 7.5</b>	1306	68%	4,136	7.2	196
		7	2	7.5	11	Aeronaut E	<b>9.5 x 5</b>	1306	68%	4,897	6.16	284
		7	2	7.5	11	Aeronaut E	<b>9.5 x 6</b>	1306	68%	4,805	6.28	248

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		7	2	7.5	11	Aeronaut E	<b>9.5 x 7</b>	1306	68%	4,445	6.78	241
		7	2	7.5	11	APC E	<b>10 x 5</b>	1306	68%	4,795	6.3	303
		7	2	7.5	11	Aeronaut E	<b>10 x 6</b>	1306	68%	4,499	6.7	276
		7	2	7.5	11	Aeronaut E	<b>10 x 7</b>	1306	68%	4,147	7.18	195
		7	2	7.5	11	APC E	<b>10 x 7</b>	1306	68%	4,202	7.11	265
		7	2	7.5	11	Aeronaut E	<b>10.5 x 6</b>	1306	68%	4,065	7.3	290
		7	2	7.5	11	Aeronaut E	<b>10.5 x 7</b>	1306	68%	3,981	7.41	269
		7	2	7.5	11	APC E	<b>11 x 5.5</b>	1306	68%	4,103	7.25	310
		7	2	7.5	11	Aeronaut E	<b>9 x 5</b>	1306	68%	4,676	6.46	272
		7	2	7.5	11	APC E	<b>9 x 6</b>	1306	68%	4,811	6.27	269
		7	2	7.5	11	APC E	<b>7 x 6</b>	1306	68%	5,951	4.71	175
<b>25 314952</b>	<b>C 28-26-09</b>	10.5	3	20	27	APC E	<b>4.75 x 5.5</b>	1935	77%	17,627	12.87	290
		10.5	3	20	27	APC E	<b>5.25 x 4.75</b>	1935	77%	16,494	17.76	405
		10.5	3	20	27	APC E	<b>5.5 x 4.5</b>	1935	77%	17,231	14.57	452
		10.5	3	20	27	APC E	<b>6 x 4</b>	1935	77%	17,302	14.27	633
		10.5	3	20	27	Aeronaut E	<b>6.5 x 4</b>	1935	77%	16,498	17.75	791
		10.5	3	20	27	APC E	<b>5 x 5</b>	1935	77%	17,566	13.13	314
		10.5	3	20	27	APC E	<b>5.1 x 4.5</b>	1935	77%	16,861	16.18	517
		7	2	20	27	APC E	<b>5.25 x 6.25</b>	1967	75%	11,858	10.21	199
		7	2	20	27	APC E	<b>5.5 x 6.25</b>	1967	75%	11,858	10.21	180
		7	2	20	27	Aeronaut E	<b>6 x 5</b>	1967	75%	11,808	10.44	310
		7	2	20	27	APC E	<b>6 x 5.5</b>	1967	75%	11,667	11.11	310
		7	2	20	27	APC E	<b>7 x 5</b>	1967	75%	10,811	15.14	551
		7	2	20	27	Aeronaut E	<b>7 x 7</b>	1967	75%	10,129	18.34	411
		7	2	20	27	APC E	<b>8 x 4</b>	1967	75%	9,899	19.42	654

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		7	2	20	27	Aeronaut E	8.5 x 5	1967	75%	10,123	18.37	639
		7	2	20	27	APC E	7 x 6	1967	75%	9,946	19.2	490
25 314953	C 28-26-12	10.5	3	16	24	APC E	5.25 x 4.75	1470	78%	13,093	8.01	255
		10.5	3	16	24	APC E	5.25 x 6.25	1470	78%	12,918	8.51	237
		10.5	3	16	24	APC E	5.5 x 6.25	1470	78%	12,918	8.51	215
		10.5	3	16	24	Aeronaut E	6 x 5	1470	78%	12,861	8.68	372
		10.5	3	16	24	APC E	6 x 5.5	1470	78%	12,678	9.21	370
		10.5	3	16	24	Aeronaut E	6.5 x 4	1470	78%	12,972	8.36	479
		10.5	3	16	24	APC E	7 x 5	1470	78%	11,627	12.25	644
		10.5	3	16	24	Aeronaut E	7 x 7	1470	78%	10,810	14.62	470
		10.5	3	16	24	APC E	8 x 4	1470	78%	10,509	15.49	742
		10.5	3	16	24	Aeronaut E	8.5 x 5	1470	78%	10,803	14.64	728
		10.5	3	16	24	APC E	7 x 6	1470	78%	10,594	15.24	556
		7	2	16	24	APC E	7 x 5	1468	74%	8,438	7.03	323
		7	2	16	24	Aeronaut E	7 x 7	1468	74%	7,987	8.56	254
		7	2	16	24	APC E	8 x 4	1468	74%	7,897	8.87	407
		7	2	16	24	APC E	8 x 6	1468	74%	7,047	11.76	389
		7	2	16	24	APC E	8 x 8	1468	74%	6,509	13.59	357
		7	2	16	24	Aeronaut E	8.5 x 5	1468	74%	7,983	8.57	397
		7	2	16	24	Aeronaut E	8.5 x 6	1468	74%	7,471	10.32	398
		7	2	16	24	Aeronaut E	8.5 x 7	1468	74%	6,953	12.08	397
		7	2	16	24	APC E	9 x 4.5	1468	74%	7,302	10.89	517
		7	2	16	24	APC E	9 x 7.5	1468	74%	5,965	15.44	427
		7	2	16	24	Aeronaut E	9.5 x 5	1468	74%	6,776	12.68	543
		7	2	16	24	Aeronaut E	9.5 x 6	1468	74%	6,675	13.02	501

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		7	2	16	24	Aeronaut E	<b>9.5 x 7</b>	1468	74%	6,265	14.42	479
		7	2	16	24	APC E	<b>10 x 5</b>	1468	74%	6,558	13.42	591
		7	2	16	24	Aeronaut E	<b>10 x 6</b>	1468	74%	6,328	14.2	547
		7	2	16	24	Aeronaut E	<b>10 x 7</b>	1468	74%	5,914	15.61	394
		7	2	16	24	APC E	<b>10 x 7</b>	1468	74%	5,870	15.76	535
		7	2	16	24	Aeronaut E	<b>10.5 x 6</b>	1468	74%	5,815	15.95	594
		7	2	16	24	Aeronaut E	<b>9 x 5</b>	1468	74%	6,530	13.52	531
		7	2	16	24	APC E	<b>9 x 6</b>	1468	74%	6,646	13.13	517
		7	2	16	24	APC E	<b>7 x 6</b>	1468	74%	7,863	8.98	306
<b>25 314954</b>	<b>C 28-26-14</b>	7	2	13	20	Aeronaut E	<b>7 x 7</b>	1276	70%	7,049	6.14	197
		7	2	13	20	APC E	<b>8 x 4</b>	1276	70%	7,002	6.27	317
		7	2	13	20	APC E	<b>8 x 6</b>	1276	70%	6,282	8.29	301
		7	2	13	20	APC E	<b>8 x 8</b>	1276	70%	5,821	9.59	282
		7	2	13	20	Aeronaut E	<b>8.5 x 5</b>	1276	70%	7,046	6.15	310
		7	2	13	20	Aeronaut E	<b>8.5 x 6</b>	1276	70%	6,612	7.36	312
		7	2	13	20	Aeronaut E	<b>8.5 x 7</b>	1276	70%	6,169	8.61	312
		7	2	13	20	APC E	<b>9 x 4.5</b>	1276	70%	6,500	7.68	403
		7	2	13	20	APC E	<b>9 x 7.5</b>	1276	70%	5,298	11.05	332
		7	2	13	20	APC E	<b>9 x 9</b>	1276	70%	4,922	12.11	314
		7	2	13	20	Aeronaut E	<b>9.5 x 5</b>	1276	70%	6,018	9.03	428
		7	2	13	20	Aeronaut E	<b>9.5 x 6</b>	1276	70%	5,931	9.28	389
		7	2	13	20	Aeronaut E	<b>9.5 x 7</b>	1276	70%	5,577	10.27	379
		7	2	13	20	APC E	<b>10 x 5</b>	1276	70%	5,863	9.47	465
		7	2	13	20	Aeronaut E	<b>10 x 6</b>	1276	70%	5,631	10.12	433
		7	2	13	20	Aeronaut E	<b>10 x 7</b>	1276	70%	5,272	11.13	314

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		7	2	13	20	APC E	10 x 7	1276	70%	5,265	11.15	426
		7	2	13	20	Aeronaut E	10 x 8	1276	70%	4,758	12.57	394
		7	2	13	20	Aeronaut E	10.5 x 6	1276	70%	5,186	11.37	472
		7	2	13	20	Aeronaut E	10.5 x 7	1276	70%	5,098	11.62	441
		7	2	13	20	Aeronaut E	10.5 x 8	1276	70%	4,924	12.11	414
		7	2	13	20	APC E	11 x 5.5	1276	70%	5,166	11.42	500
		7	2	13	20	APC E	11 x 7	1276	70%	4,822	12.39	481
		7	2	13	20	APC E	11 x 8.5	1276	70%	4,832	12.36	499
		7	2	13	20	APC E	13 x 4	1276	70%	4,817	12.41	586
		7	2	13	20	Aeronaut E	9 x 5	1276	70%	5,806	9.63	420
		7	2	13	20	APC E	12 x 6	1276	70%	4,718	12.68	568
		7	2	13	20	APC E	9 x 6	1276	70%	5,917	9.32	408
		7	2	13	20	APC E	7 x 6	1276	70%	6,945	6.43	239
		10.5	3	13	20	APC E	6 x 5.5	1287	74%	11,202	6.65	285
		10.5	3	13	20	APC E	7 x 5	1287	74%	10,287	8.81	495
		10.5	3	13	20	Aeronaut E	7 x 7	1287	74%	9,578	10.49	367
		10.5	3	13	20	APC E	8 x 4	1287	74%	9,367	10.99	583
		10.5	3	13	20	Aeronaut E	8.5 x 5	1287	74%	9,572	10.5	571
		10.5	3	13	20	Aeronaut E	8.5 x 6	1287	74%	8,809	12.31	554
		10.5	3	13	20	APC E	7 x 6	1287	74%	9,390	10.93	436
25 314955	C28-30-09	7	2	15	25	APC E	8 x 6	1198	79%	6,997	9.84	383
		7	2	15	25	APC E	8 x 8	1198	79%	6,657	12.05	374
		7	2	15	25	Aeronaut E	8.5 x 6	1198	79%	7,237	8.28	374
		7	2	15	25	Aeronaut E	8.5 x 7	1198	79%	6,940	10.21	395
		7	2	15	25	APC E	9 x 4.5	1198	79%	7,147	8.87	494

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)	
		7	2	15	25	APC E	9 x 7.5	1198	79%	6,297	14.38	479	
		7	2	15	25	Aeronaut E	9.5 x 5	1198	79%	6,832	10.91	552	
		7	2	15	25	Aeronaut E	9.5 x 6	1198	79%	6,769	11.32	516	
		7	2	15	25	Aeronaut E	9.5 x 7	1198	79%	6,500	13.07	515	
		7	2	15	25	APC E	10 x 5	1198	79%	6,690	11.83	616	
		7	2	15	25	Aeronaut E	10 x 6	1198	79%	6,542	12.79	584	
		7	2	15	25	Aeronaut E	10 x 7	1198	79%	6,254	14.66	440	
		7	2	15	25	APC E	10 x 7	1198	79%	6,209	14.95	602	
		7	2	15	25	Aeronaut E	9 x 5	1198	79%	6,676	11.92	555	
		7	2	15	25	APC E	9 x 6	1198	79%	6,749	11.45	533	
		10.5	3	15	25	APC E	7 x 5	1213	81%	11,122	9.84	586	
		10.5	3	15	25	Aeronaut E	7 x 7	1213	81%	10,659	12.37	457	
		10.5	3	15	25	APC E	8 x 4	1213	81%	10,478	13.36	737	
		10.5	3	15	25	Aeronaut E	8.5 x 5	1213	81%	10,655	12.39	708	
		10.5	3	15	25	APC E	7 x 6	1213	81%	10,529	13.08	549	
25	314956	C 28-30-12	10.5	3	12	21	Aeronaut E	7 x 7	913	77%	8,194	5.82	267
		10.5	3	12	21	APC E	8 x 4	913	77%	8,122	6.08	432	
		10.5	3	12	21	APC E	8 x 6	913	77%	7,458	8.48	441	
		10.5	3	12	21	APC E	8 x 8	913	77%	7,004	10.12	417	
		10.5	3	12	21	Aeronaut E	8.5 x 5	913	77%	8,191	5.83	418	
		10.5	3	12	21	Aeronaut E	8.5 x 6	913	77%	7,808	7.22	435	
		10.5	3	12	21	Aeronaut E	8.5 x 7	913	77%	7,397	8.7	449	
		10.5	3	12	21	APC E	9 x 4.5	913	77%	7,664	7.74	574	
		10.5	3	12	21	APC E	9 x 7.5	913	77%	6,564	11.71	523	
		10.5	3	12	21	Aeronaut E	9.5 x 5	913	77%	7,251	9.23	622	

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		10.5	3	12	21	Aeronaut E	<b>9.5 x 6</b>	913	77%	7,167	9.53	583
		10.5	3	12	21	Aeronaut E	<b>9.5 x 7</b>	913	77%	6,815	10.81	567
		10.5	3	12	21	APC E	<b>10 x 5</b>	913	77%	7,048	9.97	689
		10.5	3	12	21	Aeronaut E	<b>10 x 6</b>	913	77%	6,870	10.61	644
		10.5	3	12	21	Aeronaut E	<b>10 x 7</b>	913	77%	6,504	11.93	476
		10.5	3	12	21	Aeronaut E	<b>9 x 5</b>	913	77%	7,044	9.98	618
		10.5	3	12	21	APC E	<b>9 x 6</b>	913	77%	7,135	9.65	597
		10.5	3	12	21	APC E	<b>7 x 6</b>	913	77%	8,104	6.15	325
		14	4	12	21	APC E	<b>7 x 5</b>	923	79%	10,913	7.15	562
		14	4	12	21	Aeronaut E	<b>7 x 7</b>	923	79%	10,386	8.77	433
		14	4	12	21	APC E	<b>8 x 4</b>	923	79%	10,193	9.37	696
		14	4	12	21	Aeronaut E	<b>8.5 x 5</b>	923	79%	10,382	8.79	672
		14	4	12	21	Aeronaut E	<b>8.5 x 6</b>	923	79%	9,773	10.67	682
		14	4	12	21	APC E	<b>9 x 4.5</b>	923	79%	9,468	11.61	903
		14	4	12	21	APC E	<b>7 x 6</b>	923	79%	10,240	9.22	519
		7	2	12	21	APC E	<b>8 x 8</b>	903	72%	5,150	5.55	217
		7	2	12	21	APC E	<b>9 x 7.5</b>	903	72%	4,835	6.92	273
		7	2	12	21	APC E	<b>9 x 9</b>	903	72%	4,608	7.9	272
		7	2	12	21	Aeronaut E	<b>9.5 x 5</b>	903	72%	5,232	5.2	324
		7	2	12	21	Aeronaut E	<b>9.5 x 6</b>	903	72%	5,188	5.39	292
		7	2	12	21	Aeronaut E	<b>9.5 x 7</b>	903	72%	5,000	6.2	305
		7	2	12	21	APC E	<b>10 x 5</b>	903	72%	5,172	5.46	356
		7	2	12	21	Aeronaut E	<b>10 x 6</b>	903	72%	5,030	6.07	345
		7	2	12	21	Aeronaut E	<b>10 x 7</b>	903	72%	4,827	6.95	263
		7	2	12	21	APC E	<b>10 x 7</b>	903	72%	4,837	6.9	356

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		7	2	12	21	Aeronaut E	<b>10 x 8</b>	903	72%	4,510	8.32	353
		7	2	12	21	APC E	<b>10 x 10</b>	903	72%	4,181	9.74	342
		7	2	12	21	Aeronaut E	<b>10.5 x 6</b>	903	72%	4,776	7.17	400
		7	2	12	21	Aeronaut E	<b>10.5 x 7</b>	903	72%	4,723	7.4	378
		7	2	12	21	Aeronaut E	<b>10.5 x 8</b>	903	72%	4,616	7.86	363
		7	2	12	21	APC E	<b>11 x 5.5</b>	903	72%	4,777	7.17	425
		7	2	12	21	APC E	<b>11 x 7</b>	903	72%	4,562	8.09	427
		7	2	12	21	APC E	<b>11 x 8</b>	903	72%	4,391	8.83	433
		7	2	12	21	APC E	<b>11 x 8.5</b>	903	72%	4,580	8.02	442
		7	2	12	21	APC E	<b>11 x 10</b>	903	72%	3,896	10.97	397
		7	2	12	21	APC E	<b>12 x 8</b>	903	72%	4,115	10.03	520
		7	2	12	21	APC E	<b>12 x 10</b>	903	72%	3,713	11.77	363
		7	2	12	21	APC E	<b>13 x 4</b>	903	72%	4,558	8.11	519
		7	2	12	21	APC E	<b>13 x 6.5</b>	903	72%	4,046	10.32	543
		7	2	12	21	APC E	<b>13 x 8</b>	903	72%	3,894	10.98	523
		7	2	12	21	Aeronaut E	<b>9 x 5</b>	903	72%	5,123	5.67	327
		7	2	12	21	APC E	<b>12 x 6</b>	903	72%	4,499	8.37	513
		7	2	12	21	APC E	<b>9 x 6</b>	903	72%	5,187	5.39	313
		7	2	12	21	APC E	<b>14 x 8.5</b>	903	72%	3,663	11.98	607
		7	2	12	21	APC E v2	<b>12 x 10</b>	903	72%	3,750	11.61	370
		7	2	12	21	APC E	<b>13 x 6</b>	903	72%	4,055	10.29	582
<b>25 314957</b>	<b>C 28-30-16</b>	10.5	3	10	17	APC E	<b>8 x 6</b>	745	77%	6,567	5.44	332
		10.5	3	10	17	APC E	<b>8 x 8</b>	745	77%	6,256	6.67	328
		10.5	3	10	17	Aeronaut E	<b>8.5 x 6</b>	745	77%	6,776	4.63	328
		10.5	3	10	17	Aeronaut E	<b>8.5 x 7</b>	745	77%	6,503	5.7	347



JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		10.5	3	10	17	APC E	9 x 4.5	745	77%	6,704	4.91	431
		10.5	3	10	17	APC E	9 x 7.5	745	77%	5,905	8.05	418
		10.5	3	10	17	APC E	9 x 9	745	77%	5,612	9.2	416
		10.5	3	10	17	Aeronaut E	9.5 x 5	745	77%	6,405	6.08	485
		10.5	3	10	17	Aeronaut E	9.5 x 6	745	77%	6,346	6.31	449
		10.5	3	10	17	Aeronaut E	9.5 x 7	745	77%	6,099	7.29	454
		10.5	3	10	17	APC E	10 x 5	745	77%	6,286	6.55	540
		10.5	3	10	17	Aeronaut E	10 x 6	745	77%	6,138	7.13	514
		10.5	3	10	17	Aeronaut E	10 x 7	745	77%	5,872	8.18	388
		10.5	3	10	17	APC E	10 x 7	745	77%	5,844	8.29	530
		10.5	3	10	17	Aeronaut E	10 x 8	745	77%	5,461	9.8	518
		10.5	3	10	17	Aeronaut E	10.5 x 6	745	77%	5,806	8.44	592
		10.5	3	10	17	Aeronaut E	10.5 x 7	745	77%	5,737	8.71	558
		10.5	3	10	17	Aeronaut E	10.5 x 8	745	77%	5,597	9.26	535
		10.5	3	10	17	APC E	11 x 5.5	745	77%	5,768	8.59	628
		10.5	3	10	17	APC E	11 x 7	745	77%	5,480	9.72	633
		10.5	3	10	17	APC E	11 x 8.5	745	77%	5,454	9.82	655
		10.5	3	10	17	APC E	13 x 4	745	77%	5,477	9.73	777
		10.5	3	10	17	Aeronaut E	9 x 5	745	77%	6,261	6.65	488
		10.5	3	10	17	APC E	9 x 6	745	77%	6,332	6.37	469
		14	4	10	17	Aeronaut E	7 x 7	749	79%	9,068	5.77	328
		14	4	10	17	APC E	8 x 4	749	79%	8,971	6.12	532
		14	4	10	17	APC E	8 x 6	749	79%	8,257	8.67	552
		14	4	10	17	Aeronaut E	8.5 x 5	749	79%	9,065	5.78	512
		14	4	10	17	Aeronaut E	8.5 x 6	749	79%	8,660	7.23	535

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		14	4	10	17	Aeronaut E	<b>8.5 x 7</b>	749	79%	8,221	8.8	554
		14	4	10	17	APC E	<b>9 x 4.5</b>	749	79%	8,479	7.88	713
		14	4	10	17	Aeronaut E	<b>9.5 x 5</b>	749	79%	8,065	9.36	770
		14	4	10	17	Aeronaut E	<b>9.5 x 6</b>	749	79%	7,975	9.68	733
		14	4	10	17	APC E	<b>9 x 6</b>	749	79%	7,930	9.84	739
		14	4	10	17	APC E	<b>7 x 6</b>	749	79%	8,973	6.11	399
		17.5	5	10	17	APC E	<b>7 x 5</b>	752	79%	11,434	6.52	622
		17.5	5	10	17	Aeronaut E	<b>7 x 7</b>	752	79%	10,937	8.16	481
		17.5	5	10	17	APC E	<b>8 x 4</b>	752	79%	10,735	8.82	775
		17.5	5	10	17	Aeronaut E	<b>8.5 x 5</b>	752	79%	10,933	8.17	745
		17.5	5	10	17	APC E	<b>7 x 6</b>	752	79%	10,798	8.62	577
		7	2	10	17	APC E	<b>8 x 8</b>	736	74%	4,469	3.43	161
		7	2	10	17	APC E	<b>9 x 7.5</b>	736	74%	4,225	4.5	205
		7	2	10	17	APC E	<b>9 x 9</b>	736	74%	4,060	5.22	207
		7	2	10	17	Aeronaut E	<b>9.5 x 6</b>	736	74%	4,481	3.38	213
		7	2	10	17	Aeronaut E	<b>9.5 x 7</b>	736	74%	4,351	3.94	231
		7	2	10	17	APC E	<b>10 x 5</b>	736	74%	4,484	3.36	263
		7	2	10	17	Aeronaut E	<b>10 x 6</b>	736	74%	4,372	3.85	261
		7	2	10	17	Aeronaut E	<b>10 x 7</b>	736	74%	4,228	4.48	202
		7	2	10	17	APC E	<b>10 x 7</b>	736	74%	4,251	4.38	271
		7	2	10	17	Aeronaut E	<b>10 x 8</b>	736	74%	3,996	5.5	278
		7	2	10	17	APC E	<b>10 x 10</b>	736	74%	3,738	6.63	275
		7	2	10	17	Aeronaut E	<b>10.5 x 6</b>	736	74%	4,191	4.64	308
		7	2	10	17	Aeronaut E	<b>10.5 x 7</b>	736	74%	4,153	4.81	292
		7	2	10	17	Aeronaut E	<b>10.5 x 8</b>	736	74%	4,074	5.16	283

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		7	2	10	17	APC E	<b>11 x 5.5</b>	736	74%	4,206	4.58	326
		7	2	10	17	APC E	<b>11 x 7</b>	736	74%	4,053	5.25	332
		7	2	10	17	APC E	<b>11 x 8</b>	736	74%	3,924	5.82	348
		7	2	10	17	APC E	<b>11 x 8.5</b>	736	74%	4,084	5.11	342
		7	2	10	17	APC E	<b>11 x 10</b>	736	74%	3,540	7.5	323
		7	2	10	17	APC E	<b>12 x 8</b>	736	74%	3,698	6.81	422
		7	2	10	17	APC E	<b>12 x 10</b>	736	74%	3,393	8.14	300
		7	2	10	17	APC E	<b>12 x 12</b>	736	74%	3,028	9.74	354
		7	2	10	17	APC E	<b>13 x 4</b>	736	74%	4,049	5.27	400
		7	2	10	17	APC E	<b>13 x 6.5</b>	736	74%	3,663	6.96	443
		7	2	10	17	APC E	<b>13 x 8</b>	736	74%	3,538	7.5	421
		7	2	10	17	APC E	<b>13 x 10</b>	736	74%	3,264	8.71	383
		7	2	10	17	APC E	<b>14 x 7</b>	736	74%	3,323	8.45	463
		7	2	10	17	APC E	<b>14 x 10</b>	736	74%	3,011	9.81	467
		7	2	10	17	Aeronaut E	<b>9 x 5</b>	736	74%	4,436	3.57	245
		7	2	10	17	APC E	<b>12 x 6</b>	736	74%	4,017	5.41	401
		7	2	10	17	APC E	<b>9 x 6</b>	736	74%	4,485	3.36	233
		7	2	10	17	APC E	<b>14 x 8.5</b>	736	74%	3,352	8.32	508
		7	2	10	17	APC E v2	<b>12 x 10</b>	736	74%	3,411	8.06	303
		7	2	10	17	APC E	<b>13 x 6</b>	736	74%	3,649	7.02	471
		21	6	10	17	APC E	<b>7 x 5</b>	748	80%	13,313	8.56	862
<b>25 314958</b>	<b>C 28-34-08</b>	10.5	3	23	26	Aeronaut E	<b>7 x 7</b>	1159	78%	10,147	10.94	413
		10.5	3	23	26	APC E	<b>8 x 4</b>	1159	78%	9,990	11.7	667
		10.5	3	23	26	APC E	<b>8 x 6</b>	1159	78%	9,091	16.07	684
		10.5	3	23	26	APC E	<b>8 x 8</b>	1159	78%	8,492	18.98	627

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		10.5	3	23	26	Aeronaut E	<b>8.5 x 5</b>	1159	78%	10,143	10.96	642
		10.5	3	23	26	Aeronaut E	<b>8.5 x 6</b>	1159	78%	9,627	13.46	662
		10.5	3	23	26	Aeronaut E	<b>8.5 x 7</b>	1159	78%	9,081	16.12	676
		10.5	3	23	26	APC E	<b>9 x 4.5</b>	1159	78%	9,367	14.73	882
		10.5	3	23	26	APC E	<b>9 x 7.5</b>	1159	78%	8,038	21.19	806
		10.5	3	23	26	Aeronaut E	<b>9.5 x 5</b>	1159	78%	8,890	17.04	935
		10.5	3	23	26	Aeronaut E	<b>9.5 x 6</b>	1159	78%	8,779	17.58	901
		10.5	3	23	26	Aeronaut E	<b>9.5 x 7</b>	1159	78%	8,321	19.81	845
		10.5	3	23	26	APC E	<b>10 x 5</b>	1159	78%	8,550	18.69	1040
		10.5	3	23	26	Aeronaut E	<b>10 x 6</b>	1159	78%	8,393	19.46	962
		10.5	3	23	26	Aeronaut E	<b>10 x 7</b>	1159	78%	7,919	21.76	703
		10.5	3	23	26	APC E	<b>10 x 7</b>	1159	78%	7,762	22.53	963
		10.5	3	23	26	Aeronaut E	<b>10.5 x 6</b>	1159	78%	7,804	22.32	1071
		10.5	3	23	26	Aeronaut E	<b>10.5 x 7</b>	1159	78%	7,685	22.9	1000
		10.5	3	23	26	Aeronaut E	<b>9 x 5</b>	1159	78%	8,619	18.36	925
		10.5	3	23	26	APC E	<b>9 x 6</b>	1159	78%	8,713	17.9	894
		10.5	3	23	26	APC E	<b>7 x 6</b>	1159	78%	10,024	11.53	497
		14	4	23	26	APC E	<b>7 x 5</b>	1151	79%	13,406	13.33	875
		14	4	23	26	Aeronaut E	<b>7 x 7</b>	1151	79%	12,712	16.39	653
		14	4	23	26	APC E	<b>8 x 4</b>	1151	79%	12,371	17.89	1044
		14	4	23	26	Aeronaut E	<b>8.5 x 5</b>	1151	79%	12,706	16.41	1007
		14	4	23	26	Aeronaut E	<b>8.5 x 6</b>	1151	79%	11,914	19.91	1013
		14	4	23	26	APC E	<b>9 x 4.5</b>	1151	79%	11,425	22.07	1350
		14	4	23	26	APC E	<b>7 x 6</b>	1151	79%	12,521	17.23	776
		7	2	23	26	APC E	<b>8 x 6</b>	1142	75%	6,672	8.74	344

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		7	2	23	26	APC E	8 x 8	1142	75%	6,353	10.6	339
		7	2	23	26	Aeronaut E	8.5 x 7	1142	75%	6,610	9.1	358
		7	2	23	26	APC E	9 x 7.5	1142	75%	5,998	12.67	432
		7	2	23	26	APC E	9 x 9	1142	75%	5,698	14.42	430
		7	2	23	26	Aeronaut E	9.5 x 5	1142	75%	6,508	9.69	501
		7	2	23	26	Aeronaut E	9.5 x 6	1142	75%	6,449	10.04	465
		7	2	23	26	Aeronaut E	9.5 x 7	1142	75%	6,195	11.52	468
		7	2	23	26	APC E	10 x 5	1142	75%	6,384	10.42	558
		7	2	23	26	Aeronaut E	10 x 6	1142	75%	6,235	11.29	531
		7	2	23	26	Aeronaut E	10 x 7	1142	75%	5,963	12.87	400
		7	2	23	26	APC E	10 x 7	1142	75%	5,931	13.06	547
		7	2	23	26	Aeronaut E	10 x 8	1142	75%	5,542	15.33	534
		7	2	23	26	APC E	10 x 10	1142	75%	5,142	17.66	509
		7	2	23	26	Aeronaut E	10.5 x 6	1142	75%	5,895	13.27	610
		7	2	23	26	Aeronaut E	10.5 x 7	1142	75%	5,824	13.68	575
		7	2	23	26	Aeronaut E	10.5 x 8	1142	75%	5,681	14.51	551
		7	2	23	26	APC E	11 x 5.5	1142	75%	5,853	13.51	648
		7	2	23	26	APC E	11 x 7	1142	75%	5,558	15.23	653
		7	2	23	26	APC E	11 x 8	1142	75%	5,335	16.53	630
		7	2	23	26	APC E	11 x 8.5	1142	75%	5,528	15.41	675
		7	2	23	26	APC E	11 x 10	1142	75%	4,696	20.26	591
		7	2	23	26	APC E	12 x 8	1142	75%	5,021	18.36	768
		7	2	23	26	APC E	12 x 10	1142	75%	4,463	21.62	534
		7	2	23	26	APC E	13 x 4	1142	75%	5,555	15.25	802
		7	2	23	26	APC E	13 x 6.5	1142	75%	4,874	19.22	793

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		7	2	23	26	APC E	13 x 8	1142	75%	4,694	20.27	801
		7	2	23	26	APC E	13 x 10	1142	75%	4,265	22.77	666
		7	2	23	26	APC E	14 x 7	1142	75%	4,400	21.98	849
		7	2	23	26	Aeronaut E	9 x 5	1142	75%	6,361	10.55	504
		7	2	23	26	APC E	12 x 6	1142	75%	5,442	15.91	773
		7	2	23	26	APC E	9 x 6	1142	75%	6,433	10.13	484
		7	2	23	26	APC E	14 x 8.5	1142	75%	4,401	21.98	875
		7	2	23	26	APC E v2	12 x 10	1142	75%	4,547	21.13	556
		7	2	23	26	APC E	13 x 6	1142	75%	4,951	18.77	868
25 314959	C 28-34-10	14	4	17	22	Aeronaut E	7 x 7	912	79%	10,721	9.44	462
		14	4	17	22	APC E	8 x 4	912	79%	10,542	10.16	747
		14	4	17	22	APC E	8 x 6	912	79%	9,600	13.91	772
		14	4	17	22	APC E	8 x 8	912	79%	8,972	16.42	705
		14	4	17	22	Aeronaut E	8.5 x 5	912	79%	10,717	9.46	716
		14	4	17	22	Aeronaut E	8.5 x 6	912	79%	10,180	11.6	740
		14	4	17	22	Aeronaut E	8.5 x 7	912	79%	9,610	13.87	757
		14	4	17	22	APC E	9 x 4.5	912	79%	9,890	12.76	991
		14	4	17	22	Aeronaut E	9.5 x 5	912	79%	9,411	14.67	1048
		14	4	17	22	Aeronaut E	9.5 x 6	912	79%	9,295	15.13	1018
		14	4	17	22	APC E	10 x 5	912	79%	9,034	16.17	1169
		14	4	17	22	Aeronaut E	10 x 6	912	79%	8,890	16.75	1080
		14	4	17	22	Aeronaut E	9 x 5	912	79%	9,127	15.8	1037
		14	4	17	22	APC E	9 x 6	912	79%	9,219	15.44	1003
		14	4	17	22	APC E	7 x 6	912	79%	10,594	9.95	556
		7	2	17	22	APC E	8 x 8	897	75%	5,332	5.96	234

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		7	2	17	22	APC E	9 x 7.5	897	75%	5,058	7.48	300
		7	2	17	22	APC E	9 x 9	897	75%	4,850	8.63	304
		7	2	17	22	Aeronaut E	9.5 x 7	897	75%	5,204	6.67	330
		7	2	17	22	APC E	10 x 5	897	75%	5,352	5.85	383
		7	2	17	22	Aeronaut E	10 x 6	897	75%	5,231	6.52	373
		7	2	17	22	Aeronaut E	10 x 7	897	75%	5,048	7.53	288
		7	2	17	22	APC E	10 x 7	897	75%	5,050	7.52	390
		7	2	17	22	Aeronaut E	10 x 8	897	75%	4,754	9.16	393
		7	2	17	22	APC E	10 x 10	897	75%	4,449	10.84	385
		7	2	17	22	Aeronaut E	10.5 x 6	897	75%	5,001	7.79	439
		7	2	17	22	Aeronaut E	10.5 x 7	897	75%	4,952	8.06	416
		7	2	17	22	Aeronaut E	10.5 x 8	897	75%	4,853	8.61	402
		7	2	17	22	APC E	11 x 5.5	897	75%	4,995	7.82	466
		7	2	17	22	APC E	11 x 7	897	75%	4,794	8.94	475
		7	2	17	22	APC E	11 x 8	897	75%	4,632	9.83	480
		7	2	17	22	APC E	11 x 8.5	897	75%	4,801	8.9	492
		7	2	17	22	APC E	11 x 10	897	75%	4,154	12.48	455
		7	2	17	22	APC E	12 x 8	897	75%	4,378	11.24	587
		7	2	17	22	APC E	12 x 10	897	75%	3,973	13.48	418
		7	2	17	22	APC E	12 x 12	897	75%	3,579	15.66	489
		7	2	17	22	APC E	13 x 4	897	75%	4,791	8.96	579
		7	2	17	22	APC E	13 x 6.5	897	75%	4,297	11.69	613
		7	2	17	22	APC E	13 x 8	897	75%	4,152	12.49	606
		7	2	17	22	APC E	13 x 10	897	75%	3,816	14.35	529
		7	2	17	22	APC E	14 x 7	897	75%	3,908	13.84	657

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		7	2	17	22	APC E	<b>14 x 10</b>	897	75%	3,508	16.05	630
		7	2	17	22	Aeronaut E	<b>9 x 5</b>	897	75%	5,313	6.06	351
		7	2	17	22	APC E	<b>12 x 6</b>	897	75%	4,729	9.3	571
		7	2	17	22	APC E	<b>9 x 6</b>	897	75%	5,368	5.76	335
		7	2	17	22	APC E	<b>14 x 8.5</b>	897	75%	3,923	13.76	696
		7	2	17	22	APC E v2	<b>12 x 10</b>	897	75%	4,020	13.22	429
		7	2	17	22	APC E	<b>15 x 8</b>	897	75%	3,375	16.79	739
		7	2	17	22	APC E	<b>13 x 6</b>	897	75%	4,322	11.55	661
		10.5	3	17	22	APC E	<b>8 x 6</b>	911	79%	7,748	9.11	480
		10.5	3	17	22	APC E	<b>8 x 8</b>	911	79%	7,337	11.01	460
		10.5	3	17	22	Aeronaut E	<b>8.5 x 6</b>	911	79%	8,064	7.64	464
		10.5	3	17	22	Aeronaut E	<b>8.5 x 7</b>	911	79%	7,703	9.31	487
		10.5	3	17	22	APC E	<b>9 x 4.5</b>	911	79%	7,931	8.26	618
		10.5	3	17	22	APC E	<b>9 x 7.5</b>	911	79%	6,951	12.79	591
		10.5	3	17	22	APC E	<b>9 x 9</b>	911	79%	6,580	14.51	587
		10.5	3	17	22	Aeronaut E	<b>9.5 x 5</b>	911	79%	7,573	9.92	679
		10.5	3	17	22	Aeronaut E	<b>9.5 x 6</b>	911	79%	7,497	10.27	642
		10.5	3	17	22	Aeronaut E	<b>9.5 x 7</b>	911	79%	7,176	11.75	628
		10.5	3	17	22	APC E	<b>10 x 5</b>	911	79%	7,377	10.82	759
		10.5	3	17	22	Aeronaut E	<b>10 x 6</b>	911	79%	7,227	11.52	713
		10.5	3	17	22	Aeronaut E	<b>10 x 7</b>	911	79%	6,886	13.1	533
		10.5	3	17	22	APC E	<b>10 x 7</b>	911	79%	6,807	13.46	731
		10.5	3	17	22	Aeronaut E	<b>10 x 8</b>	911	79%	6,367	15.5	705
		10.5	3	17	22	Aeronaut E	<b>10.5 x 6</b>	911	79%	6,801	13.49	813
		10.5	3	17	22	Aeronaut E	<b>10.5 x 7</b>	911	79%	6,714	13.89	764



JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		10.5	3	17	22	Aeronaut E	<b>10.5 x 8</b>	911	79%	6,538	14.71	730
		10.5	3	17	22	APC E	<b>11 x 5.5</b>	911	79%	6,714	13.89	861
		10.5	3	17	22	APC E	<b>11 x 7</b>	911	79%	6,342	15.61	867
		10.5	3	17	22	APC E	<b>11 x 8</b>	911	79%	6,073	16.86	808
		10.5	3	17	22	APC E	<b>11 x 8.5</b>	911	79%	6,261	15.99	893
		10.5	3	17	22	APC E	<b>13 x 4</b>	911	79%	6,341	15.62	1072
		10.5	3	17	22	Aeronaut E	<b>9 x 5</b>	911	79%	7,386	10.78	679
		10.5	3	17	22	APC E	<b>12 x 6</b>	911	79%	6,174	16.39	1015
		10.5	3	17	22	APC E	<b>9 x 6</b>	911	79%	7,464	10.42	654
<b>25 314960</b>	<b>C 28-34-12</b>	7	2	14	16	APC E	<b>9 x 7.5</b>	760	75%	4,428	5.04	226
		7	2	14	16	APC E	<b>9 x 9</b>	760	75%	4,265	5.85	230
		7	2	14	16	Aeronaut E	<b>9.5 x 7</b>	760	75%	4,549	4.44	252
		7	2	14	16	Aeronaut E	<b>10 x 6</b>	760	75%	4,570	4.34	285
		7	2	14	16	Aeronaut E	<b>10 x 7</b>	760	75%	4,429	5.04	222
		7	2	14	16	APC E	<b>10 x 7</b>	760	75%	4,446	4.95	298
		7	2	14	16	Aeronaut E	<b>10 x 8</b>	760	75%	4,198	6.18	306
		7	2	14	16	APC E	<b>10 x 10</b>	760	75%	3,945	7.44	305
		7	2	14	16	Aeronaut E	<b>10.5 x 6</b>	760	75%	4,392	5.22	339
		7	2	14	16	Aeronaut E	<b>10.5 x 7</b>	760	75%	4,354	5.41	322
		7	2	14	16	Aeronaut E	<b>10.5 x 8</b>	760	75%	4,276	5.79	312
		7	2	14	16	APC E	<b>11 x 5.5</b>	760	75%	4,402	5.17	358
		7	2	14	16	APC E	<b>11 x 7</b>	760	75%	4,248	5.93	367
		7	2	14	16	APC E	<b>11 x 8</b>	760	75%	4,119	6.57	382
		7	2	14	16	APC E	<b>11 x 8.5</b>	760	75%	4,272	5.81	378
		7	2	14	16	APC E	<b>11 x 10</b>	760	75%	3,731	8.5	362

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		7	2	14	16	APC E	<b>12 x 8</b>	760	75%	3,899	7.67	468
		7	2	14	16	APC E	<b>12 x 10</b>	760	75%	3,581	9.25	336
		7	2	14	16	APC E	<b>12 x 12</b>	760	75%	3,223	11.03	399
		7	2	14	16	APC E	<b>13 x 4</b>	760	75%	4,245	5.95	444
		7	2	14	16	APC E	<b>13 x 6.5</b>	760	75%	3,854	7.89	491
		7	2	14	16	APC E	<b>13 x 8</b>	760	75%	3,730	8.51	474
		7	2	14	16	APC E	<b>13 x 10</b>	760	75%	3,450	9.9	430
		7	2	14	16	APC E	<b>14 x 7</b>	760	75%	3,517	9.57	523
		7	2	14	16	APC E	<b>14 x 10</b>	760	75%	3,190	11.19	523
		7	2	14	16	APC E	<b>12 x 6</b>	760	75%	4,208	6.13	444
		7	2	14	16	APC E	<b>14 x 8.5</b>	760	75%	3,540	9.45	567
		7	2	14	16	APC E v2	<b>12 x 10</b>	760	75%	3,607	9.12	341
		7	2	14	16	APC E	<b>15 x 8</b>	760	75%	3,059	11.84	607
		7	2	14	16	APC E	<b>16 x 8</b>	760	75%	2,779	13.23	710
		7	2	14	16	APC E	<b>17 x 8</b>	760	75%	2,642	13.91	750
		7	2	14	16	APC E	<b>13 x 6</b>	760	75%	3,851	7.91	525
		10.5	3	14	16	APC E	<b>8 x 6</b>	770	78%	6,823	6.07	362
		10.5	3	14	16	APC E	<b>8 x 8</b>	770	78%	6,504	7.41	357
		10.5	3	14	16	Aeronaut E	<b>8.5 x 7</b>	770	78%	6,765	6.31	375
		10.5	3	14	16	APC E	<b>9 x 4.5</b>	770	78%	6,962	5.48	467
		10.5	3	14	16	APC E	<b>9 x 7.5</b>	770	78%	6,157	8.87	457
		10.5	3	14	16	APC E	<b>9 x 9</b>	770	78%	5,857	10.14	457
		10.5	3	14	16	Aeronaut E	<b>9.5 x 5</b>	770	78%	6,664	6.74	525
		10.5	3	14	16	Aeronaut E	<b>9.5 x 6</b>	770	78%	6,604	6.99	490
		10.5	3	14	16	Aeronaut E	<b>9.5 x 7</b>	770	78%	6,351	8.06	492

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		10.5	3	14	16	APC E	<b>10 x 5</b>	770	78%	6,535	7.28	586
		10.5	3	14	16	Aeronaut E	<b>10 x 6</b>	770	78%	6,392	7.89	558
		10.5	3	14	16	Aeronaut E	<b>10 x 7</b>	770	78%	6,119	9.03	422
		10.5	3	14	16	APC E	<b>10 x 7</b>	770	78%	6,081	9.19	576
		10.5	3	14	16	Aeronaut E	<b>10 x 8</b>	770	78%	5,697	10.82	564
		10.5	3	14	16	APC E	<b>10 x 10</b>	770	78%	5,297	12.5	540
		10.5	3	14	16	Aeronaut E	<b>10.5 x 6</b>	770	78%	6,051	9.32	643
		10.5	3	14	16	Aeronaut E	<b>10.5 x 7</b>	770	78%	5,980	9.62	606
		10.5	3	14	16	Aeronaut E	<b>10.5 x 8</b>	770	78%	5,837	10.23	582
		10.5	3	14	16	APC E	<b>11 x 5.5</b>	770	78%	6,004	9.52	683
		10.5	3	14	16	APC E	<b>11 x 7</b>	770	78%	5,706	10.78	691
		10.5	3	14	16	APC E	<b>11 x 8</b>	770	78%	5,481	11.73	663
		10.5	3	14	16	APC E	<b>11 x 8.5</b>	770	78%	5,668	10.94	714
		10.5	3	14	16	APC E	<b>12 x 8</b>	770	78%	5,170	13.04	814
		10.5	3	14	16	APC E	<b>13 x 4</b>	770	78%	5,703	10.79	849
		10.5	3	14	16	APC E	<b>13 x 6.5</b>	770	78%	5,012	13.7	839
		10.5	3	14	16	Aeronaut E	<b>9 x 5</b>	770	78%	6,517	7.36	529
		10.5	3	14	16	APC E	<b>12 x 6</b>	770	78%	5,584	11.29	817
		10.5	3	14	16	APC E	<b>9 x 6</b>	770	78%	6,587	7.06	508
		10.5	3	14	16	APC E	<b>13 x 6</b>	770	78%	5,100	13.33	921
		14	4	14	16	APC E	<b>8 x 4</b>	776	79%	9,264	6.71	569
		14	4	14	16	APC E	<b>8 x 6</b>	776	79%	8,530	9.35	594
		14	4	14	16	APC E	<b>8 x 8</b>	776	79%	8,024	11.17	556
		14	4	14	16	Aeronaut E	<b>8.5 x 6</b>	776	79%	8,953	7.83	572
		14	4	14	16	Aeronaut E	<b>8.5 x 7</b>	776	79%	8,502	9.45	593

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		14	4	14	16	APC E	9 x 4.5	776	79%	8,758	8.53	764
		14	4	14	16	APC E	9 x 7.5	776	79%	7,605	12.68	716
		14	4	14	16	Aeronaut E	9.5 x 5	776	79%	8,342	10.02	824
		14	4	14	16	Aeronaut E	9.5 x 6	776	79%	8,249	10.36	788
		14	4	14	16	Aeronaut E	9.5 x 7	776	79%	7,860	11.76	754
		14	4	14	16	APC E	10 x 5	776	79%	8,074	10.99	920
		14	4	14	16	Aeronaut E	10 x 6	776	79%	7,921	11.54	857
		14	4	14	16	Aeronaut E	10 x 7	776	79%	7,512	13.01	633
		14	4	14	16	APC E	10 x 7	776	79%	7,391	13.45	869
		14	4	14	16	Aeronaut E	10.5 x 6	776	79%	7,411	13.37	966
		14	4	14	16	Aeronaut E	10.5 x 7	776	79%	7,308	13.75	905
		14	4	14	16	APC E	11 x 5.5	776	79%	7,284	13.83	1020
		14	4	14	16	Aeronaut E	9 x 5	776	79%	8,113	10.85	820
		14	4	14	16	APC E	9 x 6	776	79%	8,200	10.54	791
25 314961	C 35-30-10	14	4	26	35	APC E	7 x 5	1330	80%	15,198	19.13	1146
		10.5	3	26	35	Aeronaut E	7 x 7	1352	80%	11,587	15.97	541
		10.5	3	26	35	APC E	8 x 4	1352	80%	11,341	17.31	870
		10.5	3	26	35	APC E	8 x 6	1352	80%	10,221	23.45	887
		10.5	3	26	35	Aeronaut E	8.5 x 5	1352	80%	11,582	16	836
		10.5	3	26	35	Aeronaut E	8.5 x 6	1352	80%	10,934	19.54	853
		10.5	3	26	35	Aeronaut E	8.5 x 7	1352	80%	10,260	23.23	863
		10.5	3	26	35	APC E	9 x 4.5	1352	80%	10,561	21.59	1141
		10.5	3	26	35	Aeronaut E	9.5 x 5	1352	80%	10,027	24.51	1190
		10.5	3	26	35	Aeronaut E	9.5 x 6	1352	80%	9,892	25.24	1164
		10.5	3	26	35	APC E	9 x 6	1352	80%	9,795	25.78	1134

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		10.5	3	26	35	APC E	7 x 6	1352	80%	11,432	16.82	647
		7	2	26	35	APC E	8 x 6	1348	78%	7,622	13.11	463
		7	2	26	35	APC E	8 x 8	1348	78%	7,216	15.86	444
		7	2	26	35	Aeronaut E	8.5 x 6	1348	78%	7,931	11.02	449
		7	2	26	35	Aeronaut E	8.5 x 7	1348	78%	7,574	13.44	471
		7	2	26	35	APC E	9 x 4.5	1348	78%	7,803	11.89	596
		7	2	26	35	APC E	9 x 7.5	1348	78%	6,828	18.48	569
		7	2	26	35	APC E	9 x 9	1348	78%	6,462	20.95	565
		7	2	26	35	Aeronaut E	9.5 x 5	1348	78%	7,445	14.31	656
		7	2	26	35	Aeronaut E	9.5 x 6	1348	78%	7,370	14.81	619
		7	2	26	35	Aeronaut E	9.5 x 7	1348	78%	7,053	16.96	607
		7	2	26	35	APC E	10 x 5	1348	78%	7,255	15.59	733
		7	2	26	35	Aeronaut E	10 x 6	1348	78%	7,103	16.62	689
		7	2	26	35	Aeronaut E	10 x 7	1348	78%	6,766	18.9	515
		7	2	26	35	APC E	10 x 7	1348	78%	6,693	19.39	705
		7	2	26	35	Aeronaut E	10 x 8	1348	78%	6,253	22.36	680
		7	2	26	35	APC E	10 x 10	1348	78%	5,793	25.48	641
		7	2	26	35	Aeronaut E	10.5 x 6	1348	78%	6,682	19.46	785
		7	2	26	35	Aeronaut E	10.5 x 7	1348	78%	6,596	20.05	737
		7	2	26	35	Aeronaut E	10.5 x 8	1348	78%	6,422	21.22	704
		7	2	26	35	APC E	11 x 5.5	1348	78%	6,601	20.01	832
		7	2	26	35	APC E	11 x 7	1348	78%	6,235	22.49	835
		7	2	26	35	APC E	11 x 8	1348	78%	5,969	24.28	782
		7	2	26	35	APC E	11 x 8.5	1348	78%	6,161	22.99	861
		7	2	26	35	APC E	13 x 4	1348	78%	6,234	22.5	1033

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		7	2	26	35	Aeronaut E	9 x 5	1348	78%	7,260	15.56	656
		7	2	26	35	APC E	12 x 6	1348	78%	6,073	23.58	980
		7	2	26	35	APC E	9 x 6	1348	78%	7,339	15.02	632
25 314962	C 35-30-14	10.5	3	20	30	APC E	8 x 6	982	78%	8,213	10.98	546
		10.5	3	20	30	APC E	8 x 8	982	78%	7,761	13.16	518
		10.5	3	20	30	Aeronaut E	8.5 x 6	982	78%	8,576	9.22	525
		10.5	3	20	30	Aeronaut E	8.5 x 7	982	78%	8,179	11.14	549
		10.5	3	20	30	APC E	9 x 4.5	982	78%	8,415	10	701
		10.5	3	20	30	APC E	9 x 7.5	982	78%	7,367	15.07	669
		10.5	3	20	30	APC E	9 x 9	982	78%	6,965	17.02	664
		10.5	3	20	30	Aeronaut E	9.5 x 5	982	78%	8,037	11.83	764
		10.5	3	20	30	Aeronaut E	9.5 x 6	982	78%	7,953	12.24	729
		10.5	3	20	30	Aeronaut E	9.5 x 7	982	78%	7,603	13.93	705
		10.5	3	20	30	APC E	10 x 5	982	78%	7,806	12.95	856
		10.5	3	20	30	Aeronaut E	10 x 6	982	78%	7,658	13.67	801
		10.5	3	20	30	Aeronaut E	10 x 7	982	78%	7,287	15.46	596
		10.5	3	20	30	APC E	10 x 7	982	78%	7,185	15.95	819
		10.5	3	20	30	Aeronaut E	10 x 8	982	78%	6,725	18.18	786
		10.5	3	20	30	Aeronaut E	10.5 x 6	982	78%	7,195	15.9	910
		10.5	3	20	30	Aeronaut E	10.5 x 7	982	78%	7,100	16.36	854
		10.5	3	20	30	Aeronaut E	10.5 x 8	982	78%	6,910	17.28	815
		10.5	3	20	30	APC E	11 x 5.5	982	78%	7,086	16.43	963
		10.5	3	20	30	APC E	11 x 7	982	78%	6,680	18.4	969
		10.5	3	20	30	APC E	11 x 8	982	78%	6,391	19.8	891
		10.5	3	20	30	APC E	11 x 8.5	982	78%	6,574	18.91	996

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		10.5	3	20	30	APC E	<b>13 x 4</b>	982	78%	6,680	18.4	1202
		10.5	3	20	30	Aeronaut E	<b>9 x 5</b>	982	78%	7,832	12.83	764
		10.5	3	20	30	APC E	<b>12 x 6</b>	982	78%	6,487	19.33	1130
		10.5	3	20	30	APC E	<b>9 x 6</b>	982	78%	7,912	12.44	736
		14	4	20	30	Aeronaut E	<b>7 x 7</b>	987	79%	11,357	11.28	519
		14	4	20	30	APC E	<b>8 x 4</b>	987	79%	11,136	12.2	837
		14	4	20	30	APC E	<b>8 x 6</b>	987	79%	10,082	16.58	861
		14	4	20	30	Aeronaut E	<b>8.5 x 5</b>	987	79%	11,353	11.3	804
		14	4	20	30	Aeronaut E	<b>8.5 x 6</b>	987	79%	10,748	13.81	825
		14	4	20	30	Aeronaut E	<b>8.5 x 7</b>	987	79%	10,114	16.44	839
		14	4	20	30	APC E	<b>9 x 4.5</b>	987	79%	10,404	15.24	1105
		14	4	20	30	Aeronaut E	<b>9.5 x 5</b>	987	79%	9,893	17.36	1159
		14	4	20	30	Aeronaut E	<b>9.5 x 6</b>	987	79%	9,765	17.89	1132
		14	4	20	30	APC E	<b>10 x 5</b>	987	79%	9,458	19.17	1289
		14	4	20	30	Aeronaut E	<b>9 x 5</b>	987	79%	9,581	18.66	1143
		14	4	20	30	APC E	<b>9 x 6</b>	987	79%	9,674	18.27	1106
		14	4	20	30	APC E	<b>7 x 6</b>	987	79%	11,213	11.87	622
		7	2	20	30	APC E	<b>8 x 8</b>	972	76%	5,683	7.24	268
		7	2	20	30	APC E	<b>9 x 7.5</b>	972	76%	5,397	8.92	345
		7	2	20	30	APC E	<b>9 x 9</b>	972	76%	5,170	10.25	349
		7	2	20	30	Aeronaut E	<b>9.5 x 7</b>	972	76%	5,551	8.01	376
		7	2	20	30	Aeronaut E	<b>10 x 6</b>	972	76%	5,581	7.84	425
		7	2	20	30	Aeronaut E	<b>10 x 7</b>	972	76%	5,380	9.02	326
		7	2	20	30	APC E	<b>10 x 7</b>	972	76%	5,372	9.06	444
		7	2	20	30	Aeronaut E	<b>10 x 8</b>	972	76%	5,059	10.9	445

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		7	2	20	30	APC E	<b>10 x 10</b>	972	76%	4,735	12.8	434
		7	2	20	30	Aeronaut E	<b>10.5 x 6</b>	972	76%	5,329	9.32	499
		7	2	20	30	Aeronaut E	<b>10.5 x 7</b>	972	76%	5,276	9.63	472
		7	2	20	30	Aeronaut E	<b>10.5 x 8</b>	972	76%	5,167	10.27	455
		7	2	20	30	APC E	<b>11 x 5.5</b>	972	76%	5,313	9.41	530
		7	2	20	30	APC E	<b>11 x 7</b>	972	76%	5,090	10.72	541
		7	2	20	30	APC E	<b>11 x 8</b>	972	76%	4,915	11.75	537
		7	2	20	30	APC E	<b>11 x 8.5</b>	972	76%	5,085	10.75	560
		7	2	20	30	APC E	<b>11 x 10</b>	972	76%	4,395	14.79	513
		7	2	20	30	APC E	<b>12 x 8</b>	972	76%	4,649	13.31	661
		7	2	20	30	APC E	<b>12 x 10</b>	972	76%	4,200	15.94	470
		7	2	20	30	APC E	<b>12 x 12</b>	972	76%	3,796	18.31	548
		7	2	20	30	APC E	<b>13 x 4</b>	972	76%	5,087	10.74	660
		7	2	20	30	APC E	<b>13 x 6.5</b>	972	76%	4,547	13.9	688
		7	2	20	30	APC E	<b>13 x 8</b>	972	76%	4,393	14.8	689
		7	2	20	30	APC E	<b>13 x 10</b>	972	76%	4,031	16.93	592
		7	2	20	30	APC E	<b>14 x 7</b>	972	76%	4,138	16.3	743
		7	2	20	30	APC E	<b>14 x 10</b>	972	76%	3,701	18.86	700
		7	2	20	30	Aeronaut E	<b>9 x 5</b>	972	76%	5,672	7.31	400
		7	2	20	30	APC E	<b>12 x 6</b>	972	76%	5,011	11.18	647
		7	2	20	30	APC E	<b>14 x 8.5</b>	972	76%	4,147	16.25	777
		7	2	20	30	APC E v2	<b>12 x 10</b>	972	76%	4,260	15.59	484
		7	2	20	30	APC E	<b>15 x 8</b>	972	76%	3,571	19.63	827
		7	2	20	30	APC E	<b>13 x 6</b>	972	76%	4,590	13.65	746
25 <b>314963</b>	C 35-36-05	7	2	45	55	APC E	<b>8 x 8</b>	1525	78%	8,676	27.37	657



JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		7	2	45	55	APC E	<b>9 x 7.5</b>	1525	78%	8,375	31.24	879
		7	2	45	55	APC E	<b>9 x 9</b>	1525	78%	8,011	35.91	898
		7	2	45	55	Aeronaut E	<b>9.5 x 5</b>	1525	78%	8,939	23.99	946
		7	2	45	55	Aeronaut E	<b>9.5 x 6</b>	1525	78%	8,869	24.89	921
		7	2	45	55	Aeronaut E	<b>9.5 x 7</b>	1525	78%	8,566	28.78	896
		7	2	45	55	APC E	<b>10 x 5</b>	1525	78%	8,715	26.87	1083
		7	2	45	55	Aeronaut E	<b>10 x 6</b>	1525	78%	8,615	28.16	1014
		7	2	45	55	Aeronaut E	<b>10 x 7</b>	1525	78%	8,285	32.39	769
		7	2	45	55	APC E	<b>10 x 7</b>	1525	78%	8,157	34.04	1069
		7	2	45	55	Aeronaut E	<b>10 x 8</b>	1525	78%	7,763	39.09	1048
		7	2	45	55	APC E	<b>10 x 10</b>	1525	78%	7,315	44.83	1007
		7	2	45	55	Aeronaut E	<b>10.5 x 6</b>	1525	78%	8,201	33.47	1183
		7	2	45	55	Aeronaut E	<b>10.5 x 7</b>	1525	78%	8,114	34.58	1115
		7	2	45	55	Aeronaut E	<b>10.5 x 8</b>	1525	78%	7,937	36.85	1077
		7	2	45	55	APC E	<b>11 x 5.5</b>	1525	78%	8,067	35.19	1261
		7	2	45	55	APC E	<b>11 x 7</b>	1525	78%	7,673	40.25	1304
		7	2	45	55	APC E	<b>11 x 8</b>	1525	78%	7,392	43.84	1180
		7	2	45	55	APC E	<b>11 x 8.5</b>	1525	78%	7,520	42.21	1347
		7	2	45	55	APC E	<b>13 x 4</b>	1525	78%	7,675	40.22	1632
		7	2	45	55	Aeronaut E	<b>9 x 5</b>	1525	78%	8,765	26.23	957
		7	2	45	55	APC E	<b>12 x 6</b>	1525	78%	7,454	43.05	1524
		7	2	45	55	APC E	<b>9 x 6</b>	1525	78%	8,825	25.46	918
		10.5	3	45	55	APC E	<b>8 x 4</b>	1522	80%	13,510	29.74	1256
		10.5	3	45	55	APC E	<b>8 x 6</b>	1522	80%	12,420	41.58	1367
		10.5	3	45	55	Aeronaut E	<b>8.5 x 6</b>	1522	80%	13,192	33.19	1242

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		10.5	3	45	55	Aeronaut E	<b>8.5 x 7</b>	1522	80%	12,544	40.23	1290
		10.5	3	45	55	APC E	<b>9 x 4.5</b>	1522	80%	12,759	37.9	1710
		10.5	3	45	55	Aeronaut E	<b>9.5 x 5</b>	1522	80%	12,314	42.73	1795
		10.5	3	45	55	Aeronaut E	<b>9.5 x 6</b>	1522	80%	12,179	44.19	1818
		10.5	3	45	55	APC E	<b>7 x 6</b>	1522	80%	13,653	28.19	923
<b>25 314964</b>	<b>C 35-42-05</b>	10.5	3	50	65	APC E	<b>8 x 8</b>	1110	80%	9,851	26.74	859
		10.5	3	50	65	APC E	<b>9 x 7.5</b>	1110	80%	9,608	29.94	1178
		10.5	3	50	65	APC E	<b>9 x 9</b>	1110	80%	9,249	34.67	1224
		10.5	3	50	65	Aeronaut E	<b>9.5 x 7</b>	1110	80%	9,777	27.72	1167
		10.5	3	50	65	APC E	<b>10 x 5</b>	1110	80%	9,890	26.23	1418
		10.5	3	50	65	Aeronaut E	<b>10 x 6</b>	1110	80%	9,824	27.1	1319
		10.5	3	50	65	Aeronaut E	<b>10 x 7</b>	1110	80%	9,500	31.37	1009
		10.5	3	50	65	APC E	<b>10 x 7</b>	1110	80%	9,334	33.54	1419
		10.5	3	50	65	Aeronaut E	<b>10 x 8</b>	1110	80%	8,975	38.26	1400
		10.5	3	50	65	APC E	<b>10 x 10</b>	1110	80%	8,542	43.97	1359
		10.5	3	50	65	Aeronaut E	<b>10.5 x 6</b>	1110	80%	9,417	32.46	1561
		10.5	3	50	65	Aeronaut E	<b>10.5 x 7</b>	1110	80%	9,330	33.6	1474
		10.5	3	50	65	Aeronaut E	<b>10.5 x 8</b>	1110	80%	9,152	35.94	1432
		10.5	3	50	65	APC E	<b>11 x 5.5</b>	1110	80%	9,247	34.69	1675
		10.5	3	50	65	APC E	<b>11 x 7</b>	1110	80%	8,833	40.14	1764
		10.5	3	50	65	APC E	<b>11 x 8</b>	1110	80%	8,544	43.95	1559
		10.5	3	50	65	APC E	<b>11 x 8.5</b>	1110	80%	8,621	42.93	1831
		10.5	3	50	65	APC E	<b>12 x 8</b>	1110	80%	8,266	47.6	2041
		10.5	3	50	65	APC E	<b>13 x 4</b>	1110	80%	8,838	40.07	2226
		10.5	3	50	65	APC E	<b>12 x 6</b>	1110	80%	8,572	43.57	2061

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		10.5	3	50	65	APC E	<b>13 x 6</b>	1110	80%	8,194	48.55	2378
		7	2	50	65	Aeronaut E	<b>10 x 8</b>	1097	77%	6,488	21.5	732
		7	2	50	65	APC E	<b>10 x 10</b>	1097	77%	6,231	25.6	738
		7	2	50	65	APC E	<b>11 x 7</b>	1097	77%	6,471	21.77	905
		7	2	50	65	APC E	<b>11 x 8</b>	1097	77%	6,318	24.21	872
		7	2	50	65	APC E	<b>11 x 8.5</b>	1097	77%	6,421	22.57	945
		7	2	50	65	APC E	<b>11 x 10</b>	1097	77%	5,824	32.07	936
		7	2	50	65	APC E	<b>12 x 8</b>	1097	77%	6,118	27.38	1132
		7	2	50	65	APC E	<b>12 x 10</b>	1097	77%	5,625	35.24	870
		7	2	50	65	APC E	<b>12 x 12</b>	1097	77%	5,313	40.21	1051
		7	2	50	65	APC E	<b>13 x 4</b>	1097	77%	6,471	21.77	1121
		7	2	50	65	APC E	<b>13 x 6.5</b>	1097	77%	5,956	29.96	1192
		7	2	50	65	APC E	<b>13 x 8</b>	1097	77%	5,822	32.1	1307
		7	2	50	65	APC E	<b>13 x 10</b>	1097	77%	5,448	38.06	1103
		7	2	50	65	APC E	<b>14 x 7</b>	1097	77%	5,603	35.58	1430
		7	2	50	65	APC E	<b>14 x 10</b>	1097	77%	5,087	43.8	1302
		7	2	50	65	APC E	<b>12 x 6</b>	1097	77%	6,373	23.34	1087
		7	2	50	65	APC E	<b>14 x 8.5</b>	1097	77%	5,570	36.12	1402
		7	2	50	65	APC E v2	<b>12 x 10</b>	1097	77%	5,736	33.47	906
		7	2	50	65	APC E	<b>15 x 8</b>	1097	77%	5,021	44.85	1635
		7	2	50	65	APC E	<b>13 x 6</b>	1097	77%	6,071	28.14	1305
		14	4	50	65	APC E	<b>8 x 6</b>	1102	81%	12,899	33.73	1487
		14	4	50	65	APC E	<b>8 x 8</b>	1102	81%	12,269	40.96	1368
		14	4	50	65	Aeronaut E	<b>8.5 x 7</b>	1102	81%	13,014	32.41	1389
		14	4	50	65	APC E	<b>9 x 4.5</b>	1102	81%	13,177	30.55	1833

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		14	4	50	65	APC E	9 x 7.5	1102	81%	12,022	43.79	1899
		14	4	50	65	Aeronaut E	9.5 x 5	1102	81%	12,826	34.58	1948
		14	4	50	65	Aeronaut E	9.5 x 6	1102	81%	12,715	35.85	1993
		14	4	50	65	Aeronaut E	9.5 x 7	1102	81%	12,240	41.29	1830
		14	4	50	65	APC E	10 x 5	1102	81%	12,334	40.21	2271
		14	4	50	65	Aeronaut E	10 x 6	1102	81%	12,315	40.43	2073
		14	4	50	65	Aeronaut E	10 x 7	1102	81%	11,803	46.3	1553
		14	4	50	65	Aeronaut E	10.5 x 6	1102	81%	11,674	47.78	2401
		14	4	50	65	APC E	9 x 6	1102	81%	12,601	37.16	1888
25 314965	C 35-42-06	7	2	38	55	APC E	11 x 10	881	75%	4,981	19.33	670
		7	2	38	55	APC E	12 x 8	881	75%	5,168	16.66	813
		7	2	38	55	APC E	12 x 10	881	75%	4,838	21.37	633
		7	2	38	55	APC E	12 x 12	881	75%	4,568	25.24	784
		7	2	38	55	APC E	13 x 6.5	881	75%	5,082	17.89	863
		7	2	38	55	APC E	13 x 8	881	75%	4,980	19.35	916
		7	2	38	55	APC E	13 x 10	881	75%	4,708	23.23	816
		7	2	38	55	APC E	14 x 7	881	75%	4,807	21.82	1027
		7	2	38	55	APC E	14 x 10	881	75%	4,438	27.1	997
		7	2	38	55	APC E	14 x 8.5	881	75%	4,798	21.95	1041
		7	2	38	55	APC E v2	12 x 10	881	75%	4,900	20.49	650
		7	2	38	55	APC E	15 x 8	881	75%	4,362	28.19	1234
		7	2	38	55	APC E	16 x 8	881	75%	4,052	32.62	1511
		7	2	38	55	APC E	17 x 8	881	75%	3,894	34.88	1629
		7	2	38	55	APC E	13 x 6	881	75%	5,132	17.18	932
		14	4	38	55	APC E	8 x 8	901	79%	10,453	24.57	975

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		14	4	38	55	APC E	9 x 7.5	901	79%	10,196	27.1	1337
		14	4	38	55	APC E	9 x 9	901	79%	9,779	31.19	1381
		14	4	38	55	Aeronaut E	9.5 x 7	901	79%	10,383	25.26	1316
		14	4	38	55	APC E	10 x 5	901	79%	10,500	24.12	1611
		14	4	38	55	Aeronaut E	10 x 6	901	79%	10,439	24.72	1489
		14	4	38	55	Aeronaut E	10 x 7	901	79%	10,060	28.43	1131
		14	4	38	55	APC E	10 x 7	901	79%	9,850	30.49	1589
		14	4	38	55	Aeronaut E	10 x 8	901	79%	9,455	34.36	1554
		14	4	38	55	Aeronaut E	10.5 x 6	901	79%	9,963	29.38	1748
		14	4	38	55	Aeronaut E	10.5 x 7	901	79%	9,863	30.36	1647
		14	4	38	55	Aeronaut E	10.5 x 8	901	79%	9,658	32.37	1595
		14	4	38	55	APC E	11 x 5.5	901	79%	9,751	31.46	1870
		14	4	38	55	APC E	11 x 7	901	79%	9,273	36.15	1958
		14	4	38	55	APC E	13 x 4	901	79%	9,280	36.08	2478
		14	4	38	55	Aeronaut E	9 x 5	901	79%	10,611	23.03	1402
		14	4	38	55	APC E	9 x 6	901	79%	10,662	22.52	1346
		10.5	3	38	55	APC E	9 x 7.5	906	78%	8,041	18.16	806
		10.5	3	38	55	APC E	9 x 9	906	78%	7,762	21	839
		10.5	3	38	55	Aeronaut E	10 x 7	906	78%	7,977	18.82	714
		10.5	3	38	55	APC E	10 x 7	906	78%	7,886	19.74	996
		10.5	3	38	55	Aeronaut E	10 x 8	906	78%	7,571	22.95	996
		10.5	3	38	55	APC E	10 x 10	906	78%	7,207	26.66	978
		10.5	3	38	55	Aeronaut E	10.5 x 6	906	78%	7,913	19.47	1101
		10.5	3	38	55	Aeronaut E	10.5 x 7	906	78%	7,846	20.15	1043
		10.5	3	38	55	Aeronaut E	10.5 x 8	906	78%	7,709	21.55	1015

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		10.5	3	38	55	APC E	<b>11 x 5.5</b>	906	78%	7,816	20.45	1181
		10.5	3	38	55	APC E	<b>11 x 7</b>	906	78%	7,505	23.62	1243
		10.5	3	38	55	APC E	<b>11 x 8</b>	906	78%	7,276	25.95	1144
		10.5	3	38	55	APC E	<b>11 x 8.5</b>	906	78%	7,386	24.83	1294
		10.5	3	38	55	APC E	<b>11 x 10</b>	906	78%	6,568	33.16	1210
		10.5	3	38	55	APC E	<b>12 x 8</b>	906	78%	7,018	28.58	1481
		10.5	3	38	55	APC E	<b>12 x 10</b>	906	78%	6,297	35.92	1103
		10.5	3	38	55	APC E	<b>13 x 4</b>	906	78%	7,506	23.61	1554
		10.5	3	38	55	APC E	<b>13 x 6.5</b>	906	78%	6,743	31.38	1535
		10.5	3	38	55	APC E	<b>13 x 8</b>	906	78%	6,566	33.18	1719
		10.5	3	38	55	APC E	<b>14 x 7</b>	906	78%	6,289	36	1834
		10.5	3	38	55	APC E	<b>12 x 6</b>	906	78%	7,330	25.4	1470
		10.5	3	38	55	APC E	<b>14 x 8.5</b>	906	78%	6,223	36.68	1750
		10.5	3	38	55	APC E v2	<b>12 x 10</b>	906	78%	6,475	34.11	1170
		10.5	3	38	55	APC E	<b>13 x 6</b>	906	78%	6,954	29.23	1712
<b>25 314966</b>	<b>C 35-42-07</b>	10.5	3	32	45	Aeronaut E	<b>10 x 8</b>	768	78%	6,784	16.32	800
		10.5	3	32	45	APC E	<b>10 x 10</b>	768	78%	6,515	19.31	805
		10.5	3	32	45	APC E	<b>11 x 7</b>	768	78%	6,758	16.61	993
		10.5	3	32	45	APC E	<b>11 x 8</b>	768	78%	6,595	18.42	947
		10.5	3	32	45	APC E	<b>11 x 8.5</b>	768	78%	6,696	17.3	1038
		10.5	3	32	45	APC E	<b>11 x 10</b>	768	78%	6,069	24.26	1022
		10.5	3	32	45	APC E	<b>12 x 8</b>	768	78%	6,390	20.69	1232
		10.5	3	32	45	APC E	<b>12 x 10</b>	768	78%	5,859	26.59	948
		10.5	3	32	45	APC E	<b>12 x 12</b>	768	78%	5,545	30.08	1142
		10.5	3	32	45	APC E	<b>13 x 4</b>	768	78%	6,758	16.61	1234

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		10.5	3	32	45	APC E	<b>13 x 6.5</b>	768	78%	6,207	22.72	1297
		10.5	3	32	45	APC E	<b>13 x 8</b>	768	78%	6,067	24.28	1436
		10.5	3	32	45	APC E	<b>13 x 10</b>	768	78%	5,671	28.68	1198
		10.5	3	32	45	APC E	<b>14 x 7</b>	768	78%	5,842	26.78	1564
		10.5	3	32	45	APC E	<b>12 x 6</b>	768	78%	6,647	17.84	1190
		10.5	3	32	45	APC E	<b>14 x 8.5</b>	768	78%	5,800	27.24	1521
		10.5	3	32	45	APC E v2	<b>12 x 10</b>	768	78%	5,984	25.21	991
		10.5	3	32	45	APC E	<b>13 x 6</b>	768	78%	6,341	21.24	1423
		14	4	32	45	APC E	<b>9 x 7.5</b>	777	79%	9,077	19.02	1044
		14	4	32	45	APC E	<b>9 x 9</b>	777	79%	8,752	21.98	1087
		14	4	32	45	Aeronaut E	<b>10 x 7</b>	777	79%	8,987	19.84	904
		14	4	32	45	APC E	<b>10 x 7</b>	777	79%	8,851	21.08	1269
		14	4	32	45	Aeronaut E	<b>10 x 8</b>	777	79%	8,512	24.17	1259
		14	4	32	45	APC E	<b>10 x 10</b>	777	79%	8,108	27.84	1229
		14	4	32	45	Aeronaut E	<b>10.5 x 6</b>	777	79%	8,912	20.52	1397
		14	4	32	45	Aeronaut E	<b>10.5 x 7</b>	777	79%	8,833	21.24	1321
		14	4	32	45	Aeronaut E	<b>10.5 x 8</b>	777	79%	8,672	22.7	1286
		14	4	32	45	APC E	<b>11 x 5.5</b>	777	79%	8,771	21.81	1501
		14	4	32	45	APC E	<b>11 x 7</b>	777	79%	8,399	25.2	1583
		14	4	32	45	APC E	<b>11 x 8</b>	777	79%	8,134	27.61	1418
		14	4	32	45	APC E	<b>11 x 8.5</b>	777	79%	8,222	26.81	1646
		14	4	32	45	APC E	<b>12 x 8</b>	777	79%	7,865	30.06	1851
		14	4	32	45	APC E	<b>13 x 4</b>	777	79%	8,402	25.16	1991
		14	4	32	45	APC E	<b>12 x 6</b>	777	79%	8,171	27.27	1858
		14	4	32	45	APC E	<b>13 x 6</b>	777	79%	7,797	30.68	2153

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		7	2	32	45	APC E	12 x 10	753	74%	4,334	14.88	502
		7	2	32	45	APC E	12 x 12	753	74%	4,102	18.03	637
		7	2	32	45	APC E	13 x 10	753	74%	4,234	16.24	656
		7	2	32	45	APC E	14 x 7	753	74%	4,301	15.33	808
		7	2	32	45	APC E	14 x 10	753	74%	4,022	19.12	823
		7	2	32	45	APC E	14 x 8.5	753	74%	4,303	15.3	837
		7	2	32	45	APC E v2	12 x 10	753	74%	4,370	14.38	511
		7	2	32	45	APC E	15 x 8	753	74%	3,946	20.15	1010
		7	2	32	45	APC E	16 x 8	753	74%	3,695	23.56	1256
		7	2	32	45	APC E	17 x 8	753	74%	3,564	25.34	1364
		7	2	32	45	APC E	17 x 10	753	74%	3,310	28.78	1277
25 4967	C 35-48-05	10.5	3	45	60	Aeronaut E	10 x 8	833	80%	7,425	20.86	958
		10.5	3	45	60	APC E	10 x 10	833	80%	7,152	24.7	964
		10.5	3	45	60	APC E	11 x 7	833	80%	7,380	21.5	1199
		10.5	3	45	60	APC E	11 x 8	833	80%	7,208	23.91	1124
		10.5	3	45	60	APC E	11 x 8.5	833	80%	7,294	22.7	1258
		10.5	3	45	60	APC E	11 x 10	833	80%	6,646	31.79	1240
		10.5	3	45	60	APC E	12 x 8	833	80%	7,007	26.73	1476
		10.5	3	45	60	APC E	12 x 10	833	80%	6,420	34.96	1149
		10.5	3	45	60	APC E	12 x 12	833	80%	6,122	39.14	1383
		10.5	3	45	60	APC E	13 x 4	833	80%	7,381	21.48	1498
		10.5	3	45	60	APC E	13 x 6.5	833	80%	6,788	29.8	1556
		10.5	3	45	60	APC E	13 x 8	833	80%	6,644	31.82	1766
		10.5	3	45	60	APC E	13 x 10	833	80%	6,218	37.79	1449
		10.5	3	45	60	APC E	14 x 7	833	80%	6,417	35	1915



JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		10.5	3	45	60	APC E	<b>14 x 10</b>	833	80%	5,808	43.54	1687
		10.5	3	45	60	APC E	<b>12 x 6</b>	833	80%	7,250	23.32	1436
		10.5	3	45	60	APC E	<b>14 x 8.5</b>	833	80%	6,357	35.84	1827
		10.5	3	45	60	APC E v2	<b>12 x 10</b>	833	80%	6,572	32.83	1207
		10.5	3	45	60	APC E	<b>15 x 8</b>	833	80%	5,771	44.06	2160
		10.5	3	45	60	APC E	<b>13 x 6</b>	833	80%	6,957	27.42	1714
		14	4	45	60	APC E	<b>9 x 7.5</b>	844	80%	9,950	24.51	1269
		14	4	45	60	APC E	<b>9 x 9</b>	844	80%	9,615	28.46	1331
		14	4	45	60	Aeronaut E	<b>10 x 7</b>	844	80%	9,844	25.75	1083
		14	4	45	60	APC E	<b>10 x 7</b>	844	80%	9,680	27.7	1532
		14	4	45	60	Aeronaut E	<b>10 x 8</b>	844	80%	9,350	31.58	1520
		14	4	45	60	APC E	<b>10 x 10</b>	844	80%	8,944	36.38	1485
		14	4	45	60	Aeronaut E	<b>10.5 x 6</b>	844	80%	9,767	26.67	1679
		14	4	45	60	Aeronaut E	<b>10.5 x 7</b>	844	80%	9,686	27.63	1588
		14	4	45	60	Aeronaut E	<b>10.5 x 8</b>	844	80%	9,518	29.6	1549
		14	4	45	60	APC E	<b>11 x 5.5</b>	844	80%	9,598	28.66	1810
		14	4	45	60	APC E	<b>11 x 7</b>	844	80%	9,201	33.35	1925
		14	4	45	60	APC E	<b>11 x 8</b>	844	80%	8,922	36.63	1695
		14	4	45	60	APC E	<b>11 x 8.5</b>	844	80%	8,981	35.95	2007
		14	4	45	60	APC E	<b>12 x 8</b>	844	80%	8,666	39.66	2239
		14	4	45	60	APC E	<b>13 x 4</b>	844	80%	9,207	33.28	2435
		14	4	45	60	APC E	<b>13 x 6.5</b>	844	80%	8,242	44.66	2310
		14	4	45	60	APC E	<b>12 x 6</b>	844	80%	8,940	36.43	2256
		14	4	45	60	APC E	<b>13 x 6</b>	844	80%	8,598	40.46	2618
		7	2	45	60	APC E	<b>11 x 10</b>	820	77%	4,863	17.31	637

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		7	2	45	60	APC E	12 x 10	820	77%	4,747	19.3	608
		7	2	45	60	APC E	12 x 12	820	77%	4,520	23.2	768
		7	2	45	60	APC E	13 x 8	820	77%	4,862	17.33	867
		7	2	45	60	APC E	13 x 10	820	77%	4,640	21.14	792
		7	2	45	60	APC E	14 x 7	820	77%	4,720	19.77	987
		7	2	45	60	APC E	14 x 10	820	77%	4,412	25.06	986
		7	2	45	60	APC E	14 x 8.5	820	77%	4,714	19.87	1004
		7	2	45	60	APC E v2	12 x 10	820	77%	4,795	18.48	621
		7	2	45	60	APC E	15 x 8	820	77%	4,346	26.19	1225
		7	2	45	60	APC E	16 x 8	820	77%	4,077	30.82	1529
		7	2	45	60	APC E	17 x 8	820	77%	3,936	33.24	1664
		7	2	45	60	APC E	17 x 10	820	77%	3,662	37.96	1562
25 4968	C 42-40-10	10.5	3	40	50	APC E	8 x 8	1035	82%	9,194	20.82	742
		10.5	3	40	50	APC E	9 x 7.5	1035	82%	8,958	23.76	1015
		10.5	3	40	50	APC E	9 x 9	1035	82%	8,642	27.72	1057
		10.5	3	40	50	Aeronaut E	9.5 x 7	1035	82%	9,114	21.82	1014
		10.5	3	40	50	APC E	10 x 5	1035	82%	9,228	20.4	1223
		10.5	3	40	50	Aeronaut E	10 x 6	1035	82%	9,155	21.31	1145
		10.5	3	40	50	Aeronaut E	10 x 7	1035	82%	8,872	24.84	881
		10.5	3	40	50	APC E	10 x 7	1035	82%	8,743	26.46	1237
		10.5	3	40	50	Aeronaut E	10 x 8	1035	82%	8,410	30.62	1229
		10.5	3	40	50	APC E	10 x 10	1035	82%	8,014	35.56	1201
		10.5	3	40	50	Aeronaut E	10.5 x 6	1035	82%	8,799	25.75	1362
		10.5	3	40	50	Aeronaut E	10.5 x 7	1035	82%	8,723	26.71	1289
		10.5	3	40	50	Aeronaut E	10.5 x 8	1035	82%	8,566	28.66	1254

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		10.5	3	40	50	APC E	<b>11 x 5.5</b>	1035	82%	8,665	27.43	1463
		10.5	3	40	50	APC E	<b>11 x 7</b>	1035	82%	8,303	31.95	1545
		10.5	3	40	50	APC E	<b>11 x 8</b>	1035	82%	8,045	35.18	1389
		10.5	3	40	50	APC E	<b>11 x 8.5</b>	1035	82%	8,135	34.06	1607
		10.5	3	40	50	APC E	<b>12 x 8</b>	1035	82%	7,780	38.5	1812
		10.5	3	40	50	APC E	<b>13 x 4</b>	1035	82%	8,307	31.91	1942
		10.5	3	40	50	Aeronaut E	<b>9 x 5</b>	1035	82%	9,281	19.72	1073
		10.5	3	40	50	APC E	<b>12 x 6</b>	1035	82%	8,084	34.69	1816
		10.5	3	40	50	APC E	<b>13 x 6</b>	1035	82%	7,712	39.34	2106
		7	2	40	50	Aeronaut E	<b>10 x 8</b>	1021	80%	6,062	16.99	639
		7	2	40	50	APC E	<b>10 x 10</b>	1021	80%	5,834	20.53	650
		7	2	40	50	APC E	<b>11 x 7</b>	1021	80%	6,057	17.05	785
		7	2	40	50	APC E	<b>11 x 8</b>	1021	80%	5,925	19.1	770
		7	2	40	50	APC E	<b>11 x 8.5</b>	1021	80%	6,025	17.55	819
		7	2	40	50	APC E	<b>11 x 10</b>	1021	80%	5,495	25.8	827
		7	2	40	50	APC E	<b>12 x 8</b>	1021	80%	5,743	21.94	1000
		7	2	40	50	APC E	<b>12 x 10</b>	1021	80%	5,320	28.53	773
		7	2	40	50	APC E	<b>12 x 12</b>	1021	80%	5,023	33.14	943
		7	2	40	50	APC E	<b>13 x 4</b>	1021	80%	6,057	17.06	969
		7	2	40	50	APC E	<b>13 x 6.5</b>	1021	80%	5,615	23.94	1057
		7	2	40	50	APC E	<b>13 x 8</b>	1021	80%	5,494	25.82	1145
		7	2	40	50	APC E	<b>13 x 10</b>	1021	80%	5,162	30.99	987
		7	2	40	50	APC E	<b>14 x 7</b>	1021	80%	5,293	28.94	1264
		7	2	40	50	APC E	<b>14 x 10</b>	1021	80%	4,838	36.02	1181
		7	2	40	50	APC E	<b>12 x 6</b>	1021	80%	5,980	18.26	947

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		7	2	40	50	APC E	14 x 8.5	1021	80%	5,271	29.29	1256
		7	2	40	50	APC E v2	12 x 10	1021	80%	5,409	27.13	801
		7	2	40	50	APC E	15 x 8	1021	80%	4,767	37.13	1474
		7	2	40	50	APC E	13 x 6	1021	80%	5,700	22.61	1150
		14	4	40	50	APC E	8 x 6	1034	83%	12,073	26.67	1284
		14	4	40	50	APC E	8 x 8	1034	83%	11,516	32.72	1197
		14	4	40	50	Aeronaut E	8.5 x 7	1034	83%	12,153	25.8	1211
		14	4	40	50	APC E	9 x 4.5	1034	83%	12,316	24.02	1585
		14	4	40	50	APC E	9 x 7.5	1034	83%	11,260	35.52	1652
		14	4	40	50	Aeronaut E	9.5 x 5	1034	83%	11,987	27.61	1701
		14	4	40	50	Aeronaut E	9.5 x 6	1034	83%	11,888	28.68	1726
		14	4	40	50	Aeronaut E	9.5 x 7	1034	83%	11,467	33.26	1606
		14	4	40	50	APC E	10 x 5	1034	83%	11,574	32.1	1982
		14	4	40	50	Aeronaut E	10 x 6	1034	83%	11,534	32.53	1818
		14	4	40	50	Aeronaut E	10 x 7	1034	83%	11,077	37.5	1369
		14	4	40	50	Aeronaut E	10.5 x 6	1034	83%	10,962	38.76	2116
		14	4	40	50	Aeronaut E	9 x 5	1034	83%	11,743	30.25	1718
		14	4	40	50	APC E	9 x 6	1034	83%	11,795	29.69	1652
25 314969	C 42-40-12	10.5	3	35	40	APC E	9 x 7.5	863	81%	7,724	15.51	740
		10.5	3	35	40	APC E	9 x 9	863	81%	7,496	18.2	778
		10.5	3	35	40	Aeronaut E	10 x 7	863	81%	7,676	16.09	661
		10.5	3	35	40	APC E	10 x 7	863	81%	7,608	16.89	923
		10.5	3	35	40	Aeronaut E	10 x 8	863	81%	7,340	20.03	937
		10.5	3	35	40	APC E	10 x 10	863	81%	7,030	23.69	932
		10.5	3	35	40	Aeronaut E	10.5 x 6	863	81%	7,624	16.7	1022

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		10.5	3	35	40	Aeronaut E	<b>10.5 x 7</b>	863	81%	7,569	17.35	970
		10.5	3	35	40	Aeronaut E	<b>10.5 x 8</b>	863	81%	7,455	18.68	950
		10.5	3	35	40	APC E	<b>11 x 5.5</b>	863	81%	7,550	17.57	1099
		10.5	3	35	40	APC E	<b>11 x 7</b>	863	81%	7,292	20.6	1169
		10.5	3	35	40	APC E	<b>11 x 8</b>	863	81%	7,098	22.89	1091
		10.5	3	35	40	APC E	<b>11 x 8.5</b>	863	81%	7,198	21.7	1221
		10.5	3	35	40	APC E	<b>11 x 10</b>	863	81%	6,482	30.14	1176
		10.5	3	35	40	APC E	<b>12 x 8</b>	863	81%	6,871	25.55	1421
		10.5	3	35	40	APC E	<b>12 x 10</b>	863	81%	6,239	32.99	1082
		10.5	3	35	40	APC E	<b>13 x 4</b>	863	81%	7,293	20.59	1458
		10.5	3	35	40	APC E	<b>13 x 6.5</b>	863	81%	6,637	28.31	1486
		10.5	3	35	40	APC E	<b>13 x 8</b>	863	81%	6,479	30.17	1668
		10.5	3	35	40	APC E	<b>14 x 7</b>	863	81%	6,231	33.09	1797
		10.5	3	35	40	APC E	<b>12 x 6</b>	863	81%	7,148	22.3	1392
		10.5	3	35	40	APC E	<b>14 x 8.5</b>	863	81%	6,172	33.78	1722
		10.5	3	35	40	APC E v2	<b>12 x 10</b>	863	81%	6,396	31.15	1140
		10.5	3	35	40	APC E	<b>13 x 6</b>	863	81%	6,816	26.21	1645
		14	4	35	40	APC E	<b>8 x 8</b>	871	82%	10,067	21	900
		14	4	35	40	APC E	<b>9 x 7.5</b>	871	82%	9,827	23.52	1236
		14	4	35	40	APC E	<b>9 x 9</b>	871	82%	9,458	27.37	1285
		14	4	35	40	Aeronaut E	<b>9.5 x 6</b>	871	82%	10,297	18.6	1268
		14	4	35	40	Aeronaut E	<b>9.5 x 7</b>	871	82%	9,996	21.74	1220
		14	4	35	40	APC E	<b>10 x 5</b>	871	82%	10,108	20.58	1485
		14	4	35	40	Aeronaut E	<b>10 x 6</b>	871	82%	10,045	21.24	1379
		14	4	35	40	Aeronaut E	<b>10 x 7</b>	871	82%	9,712	24.71	1055

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		14	4	35	40	APC E	<b>10 x 7</b>	871	82%	9,536	26.55	1485
		14	4	35	40	Aeronaut E	<b>10 x 8</b>	871	82%	9,175	30.33	1463
		14	4	35	40	Aeronaut E	<b>10.5 x 6</b>	871	82%	9,627	25.6	1631
		14	4	35	40	Aeronaut E	<b>10.5 x 7</b>	871	82%	9,538	26.53	1540
		14	4	35	40	Aeronaut E	<b>10.5 x 8</b>	871	82%	9,356	28.44	1497
		14	4	35	40	APC E	<b>11 x 5.5</b>	871	82%	9,447	27.48	1751
		14	4	35	40	APC E	<b>11 x 7</b>	871	82%	9,021	31.94	1845
		14	4	35	40	APC E	<b>13 x 4</b>	871	82%	9,027	31.88	2331
		14	4	35	40	Aeronaut E	<b>9 x 5</b>	871	82%	10,194	19.68	1294
		14	4	35	40	APC E	<b>9 x 6</b>	871	82%	10,242	19.18	1241
		7	2	35	40	APC E	<b>10 x 10</b>	853	79%	5,039	13.42	490
		7	2	35	40	APC E	<b>11 x 8</b>	853	79%	5,133	12.11	584
		7	2	35	40	APC E	<b>11 x 10</b>	853	79%	4,812	16.6	623
		7	2	35	40	APC E	<b>12 x 8</b>	853	79%	4,983	14.21	757
		7	2	35	40	APC E	<b>12 x 10</b>	853	79%	4,678	18.48	590
		7	2	35	40	APC E	<b>12 x 12</b>	853	79%	4,415	22.18	734
		7	2	35	40	APC E	<b>13 x 6.5</b>	853	79%	4,908	15.26	804
		7	2	35	40	APC E	<b>13 x 8</b>	853	79%	4,811	16.62	847
		7	2	35	40	APC E	<b>13 x 10</b>	853	79%	4,556	20.2	763
		7	2	35	40	APC E	<b>14 x 7</b>	853	79%	4,645	18.95	954
		7	2	35	40	APC E	<b>14 x 10</b>	853	79%	4,300	23.78	938
		7	2	35	40	APC E	<b>14 x 8.5</b>	853	79%	4,640	19.02	973
		7	2	35	40	APC E v2	<b>12 x 10</b>	853	79%	4,732	17.73	604
		7	2	35	40	APC E	<b>15 x 8</b>	853	79%	4,222	24.88	1156
		7	2	35	40	APC E	<b>16 x 8</b>	853	79%	3,928	29	1420

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		7	2	35	40	APC E	17 x 8	853	79%	3,777	31.12	1532
		7	2	35	40	APC E	13 x 6	853	79%	4,948	14.7	867
25 314970	C 42-50-05	10.5	3	65	80	Aeronaut E	10 x 8	1029	81%	9,170	38.84	1462
		10.5	3	65	80	APC E	10 x 10	1029	81%	8,875	45.62	1463
		10.5	3	65	80	APC E	11 x 7	1029	81%	9,067	41.21	1865
		10.5	3	65	80	APC E	11 x 8	1029	81%	8,862	45.92	1673
		10.5	3	65	80	APC E	11 x 8.5	1029	81%	8,908	44.87	1971
		10.5	3	65	80	APC E	11 x 10	1029	81%	8,184	61.51	1934
		10.5	3	65	80	APC E	12 x 8	1029	81%	8,669	50.36	2240
		10.5	3	65	80	APC E	13 x 4	1029	81%	9,071	41.12	2356
		10.5	3	65	80	APC E	13 x 6.5	1029	81%	8,338	57.98	2365
		10.5	3	65	80	APC E	13 x 8	1029	81%	8,182	61.57	2836
		10.5	3	65	80	APC E	12 x 6	1029	81%	8,876	45.59	2222
		10.5	3	65	80	APC E v2	12 x 10	1029	81%	8,142	62.48	1896
		10.5	3	65	80	APC E	13 x 6	1029	81%	8,618	51.54	2630
		14	4	65	80	APC E	9 x 7.5	1029	81%	12,292	44.75	1991
		14	4	65	80	APC E	9 x 9	1029	81%	11,905	52.32	2111
		14	4	65	80	Aeronaut E	10 x 7	1029	81%	12,137	47.77	1642
		14	4	65	80	APC E	10 x 7	1029	81%	11,881	52.8	2357
		14	4	65	80	Aeronaut E	10 x 8	1029	81%	11,560	59.1	2323
		14	4	65	80	Aeronaut E	10.5 x 6	1029	81%	12,047	49.55	2557
		14	4	65	80	Aeronaut E	10.5 x 7	1029	81%	11,952	51.41	2418
		14	4	65	80	Aeronaut E	10.5 x 8	1029	81%	11,756	55.25	2366
		14	4	65	80	APC E	11 x 5.5	1029	81%	11,790	54.59	2774
		14	4	65	80	APC E	11 x 7	1029	81%	11,300	64.19	2992

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		14	4	65	80	APC E	13 x 4	1029	81%	11,311	63.97	3829
		17.5	5	65	80	APC E	8 x 6	1024	81%	15,410	47.46	2207
		17.5	5	65	80	Aeronaut E	9.5 x 5	1024	81%	15,402	47.61	2809
		17.5	5	65	80	Aeronaut E	9.5 x 6	1024	81%	15,297	49.54	2963
		17.5	5	65	80	APC E	9 x 6	1024	81%	15,167	51.96	2748
25 314971	C 42-50-06	14	4	58	70	Aeronaut E	10 x 8	810	82%	9,628	33.11	1611
		14	4	58	70	APC E	10 x 10	810	82%	9,324	38.72	1610
		14	4	58	70	APC E	11 x 7	810	82%	9,507	35.34	2065
		14	4	58	70	APC E	11 x 8	810	82%	9,292	39.32	1833
		14	4	58	70	APC E	11 x 8.5	810	82%	9,325	38.7	2184
		14	4	58	70	APC E	11 x 10	810	82%	8,576	52.54	2137
		14	4	58	70	APC E	12 x 8	810	82%	9,099	42.88	2463
		14	4	58	70	APC E	12 x 10	810	82%	8,287	57.87	1967
		14	4	58	70	APC E	13 x 4	810	82%	9,512	35.25	2616
		14	4	58	70	APC E	13 x 6.5	810	82%	8,734	49.62	2599
		14	4	58	70	APC E	13 x 8	810	82%	8,573	52.59	3154
		14	4	58	70	APC E	14 x 7	810	82%	8,335	56.97	3367
		14	4	58	70	APC E	12 x 6	810	82%	9,298	39.21	2456
		14	4	58	70	APC E v2	12 x 10	810	82%	8,542	53.15	2097
		14	4	58	70	APC E	13 x 6	810	82%	9,047	43.84	2899
		17.5	5	58	70	APC E	9 x 9	809	82%	11,844	40.53	2088
		17.5	5	58	70	Aeronaut E	10 x 7	809	82%	12,060	36.99	1621
		17.5	5	58	70	APC E	10 x 7	809	82%	11,823	40.87	2334
		17.5	5	58	70	Aeronaut E	10 x 8	809	82%	11,522	45.8	2308
		17.5	5	58	70	Aeronaut E	10.5 x 6	809	82%	11,976	38.36	2527



JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		17.5	5	58	70	Aeronaut E	<b>10.5 x 7</b>	809	82%	11,888	39.81	2392
		17.5	5	58	70	Aeronaut E	<b>10.5 x 8</b>	809	82%	11,706	42.79	2345
		17.5	5	58	70	APC E	<b>11 x 5.5</b>	809	82%	11,738	42.27	2749
		10.5	3	58	70	APC E	<b>11 x 10</b>	803	81%	6,933	34.17	1357
		10.5	3	58	70	APC E	<b>12 x 8</b>	803	81%	7,216	28.07	1564
		10.5	3	58	70	APC E	<b>12 x 10</b>	803	81%	6,751	38.08	1278
		10.5	3	58	70	APC E	<b>12 x 12</b>	803	81%	6,525	42.94	1565
		10.5	3	58	70	APC E	<b>13 x 6.5</b>	803	81%	7,042	31.82	1677
		10.5	3	58	70	APC E	<b>13 x 8</b>	803	81%	6,931	34.21	1944
		10.5	3	58	70	APC E	<b>13 x 10</b>	803	81%	6,585	41.66	1630
		10.5	3	58	70	APC E	<b>14 x 7</b>	803	81%	6,755	37.99	2140
		10.5	3	58	70	APC E	<b>14 x 10</b>	803	81%	6,235	49.2	1938
		10.5	3	58	70	APC E	<b>14 x 8.5</b>	803	81%	6,700	39.18	2029
		10.5	3	58	70	APC E v2	<b>12 x 10</b>	803	81%	6,880	35.3	1330
		10.5	3	58	70	APC E	<b>15 x 8</b>	803	81%	6,220	49.52	2509
		10.5	3	58	70	APC E	<b>13 x 6</b>	803	81%	7,180	28.86	1825
<b>25 314972</b>	<b>C 42-60-05</b>	14	4	58	85	APC E	<b>11 x 10</b>	705	81%	8,096	42.15	1890
		14	4	58	85	APC E	<b>12 x 10</b>	705	81%	7,884	46.93	1771
		14	4	58	85	APC E	<b>12 x 12</b>	705	81%	7,684	51.45	2148
		14	4	58	85	APC E	<b>13 x 6.5</b>	705	81%	8,213	39.49	2293
		14	4	58	85	APC E	<b>13 x 8</b>	705	81%	8,094	42.19	2767
		14	4	58	85	APC E	<b>13 x 10</b>	705	81%	7,689	51.32	2245
		14	4	58	85	APC E	<b>14 x 7</b>	705	81%	7,912	46.29	3009
		14	4	58	85	APC E	<b>14 x 8.5</b>	705	81%	7,824	48.28	2767
		14	4	58	85	APC E v2	<b>12 x 10</b>	705	81%	8,062	42.91	1856

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		17.5	5	58	85	APC E	10 x 10	707	81%	10,389	42.42	1984
		17.5	5	58	85	APC E	11 x 8	707	81%	10,313	43.94	2241
		17.5	5	58	85	APC E	11 x 8.5	707	81%	10,315	43.9	2739
		17.5	5	58	85	APC E	12 x 8	707	81%	10,142	47.39	3047
		17.5	5	58	85	APC E	13 x 6.5	707	81%	9,725	55.77	3235
		17.5	5	58	85	APC E	12 x 6	707	81%	10,299	44.23	3062
		17.5	5	58	85	APC E	13 x 6	707	81%	10,092	48.39	3608
		10.5	3	58	85	APC E	12 x 12	699	80%	6,107	34.68	1377
		10.5	3	58	85	APC E	13 x 10	699	80%	6,165	33.15	1423
		10.5	3	58	85	APC E	14 x 10	699	80%	5,912	39.81	1746
		10.5	3	58	85	APC E	14 x 8.5	699	80%	6,246	31.03	1763
		10.5	3	58	85	APC E	15 x 8	699	80%	5,891	40.35	2251
		10.5	3	58	85	APC E	16 x 8	699	80%	5,589	48.29	2874
		10.5	3	58	85	APC E	17 x 8	699	80%	5,426	52.56	3162
25 314973	C 42-60-06	10.5	3	47	75	APC E	12 x 12	637	80%	5,653	27.57	1185
		10.5	3	47	75	APC E	14 x 10	637	80%	5,504	31.31	1519
		10.5	3	47	75	APC E	15 x 8	637	80%	5,476	32.03	1945
		10.5	3	47	75	APC E	16 x 8	637	80%	5,217	38.56	2504
		10.5	3	47	75	APC E	17 x 8	637	80%	5,076	42.12	2768
		14	4	47	75	APC E	11 x 10	644	81%	7,520	32.92	1615
		14	4	47	75	APC E	12 x 10	644	81%	7,340	36.76	1524
		14	4	47	75	APC E	12 x 12	644	81%	7,144	40.94	1865
		14	4	47	75	APC E	13 x 6.5	644	81%	7,623	30.71	1970
		14	4	47	75	APC E	13 x 8	644	81%	7,518	32.95	2339
		14	4	47	75	APC E	13 x 10	644	81%	7,174	40.31	1945

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		14	4	47	75	APC E	14 x 7	644	81%	7,355	36.44	2571
		14	4	47	75	APC E	14 x 8.5	644	81%	7,289	37.85	2401
		14	4	47	75	APC E v2	12 x 10	644	81%	7,480	33.76	1586
		17.5	5	47	75	APC E	11 x 8	649	82%	9,553	34.02	1933
		17.5	5	47	75	APC E	11 x 8.5	649	82%	9,575	33.61	2318
		17.5	5	47	75	APC E	11 x 10	649	82%	8,904	45.87	2316
		17.5	5	47	75	APC E	12 x 8	649	82%	9,387	37.04	2618
		17.5	5	47	75	APC E	13 x 6.5	649	82%	9,046	43.27	2792
		17.5	5	47	75	APC E	13 x 8	649	82%	8,902	45.92	3436
		17.5	5	47	75	APC E	12 x 6	649	82%	9,553	34.01	2604
		17.5	5	47	75	APC E v2	12 x 10	649	82%	8,882	46.28	2277
		17.5	5	47	75	APC E	13 x 6	649	82%	9,342	37.88	3091
25 314974	C 50-55-06	14	4	60	90	APC E	12 x 8	769	83%	9,483	47.27	2671
		14	4	60	90	APC E	13 x 6.5	769	83%	9,221	56.59	2903
		14	4	60	90	APC E	13 x 6	769	83%	9,450	48.47	3163
		10.5	3	60	90	APC E	12 x 10	763	82%	7,031	42.16	1392
		10.5	3	60	90	APC E	12 x 12	763	82%	6,885	48.08	1737
		10.5	3	60	90	APC E	13 x 10	763	82%	6,915	46.88	1803
		10.5	3	60	90	APC E	14 x 7	763	82%	7,037	41.91	2337
		10.5	3	60	90	APC E	14 x 10	763	82%	6,659	57.27	2204
		10.5	3	60	90	APC E	14 x 8.5	763	82%	6,996	43.6	2212
		10.5	3	60	90	APC E	15 x 8	763	82%	6,660	57.23	2877
		17.5	5	60	90	Aeronaut E	10 x 8	769	83%	11,990	50.67	2499
		17.5	5	60	90	APC E	10 x 10	769	83%	11,725	59.24	2506
		17.5	5	60	90	APC E	11 x 7	769	83%	11,819	56.21	3294

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		17.5	5	60	90	APC E	13 x 4	769	83%	11,826	55.96	4223
25 314984	C 50-55-45	24.5	7	16	18	APC E	22 x 10	98	83%	2,113	4.1	1126
25 314975	C 50-65-07	17.5	5	52	90	APC E	16 x 8	434	85%	6,653	43.94	4073
		17.5	5	52	90	APC E	17 x 8	434	85%	6,540	48.98	4595
		21	6	52	90	APC E	14 x 10	436	85%	7,987	48.32	3144
		21	6	52	90	APC E	15 x 8	436	85%	8,019	47.07	4170
		14	4	52	90	APC E	17 x 8	432	85%	5,394	34.19	3126
		14	4	52	90	APC E	17 x 10	432	85%	5,237	41.99	3195
25 314976	C 63-62-08	21	6	80	90	APC E	22 x 10	320	85%	5,281	76.23	7873
		21	6	80	90	APC E	20 x 10	320	85%	5,560	61.03	6451
		24.5	7	80	90	APC E	17 x 10	322	85%	6,759	51.26	5322
		28	8	80	90	APC E	14 x 10	334	82%	8,045	38.54	3189
		28	8	80	90	APC E	16 x 8	334	82%	7,727	45.05	5494
		28	8	80	90	APC E	17 x 8	334	82%	7,529	49.1	6089
		28	8	80	90	APC E	17 x 10	334	82%	7,127	57.33	5918
		31.5	9	80	90	APC E	14 x 10	334	83%	8,724	44.13	3736
		31.5	9	80	90	APC E	15 x 8	334	83%	8,792	42.68	5013
		31.5	9	80	90	APC E	16 x 8	334	83%	8,385	51.3	6470
25 314977	C 63-62-10	24.5	7	70	80	APC E	22 x 10	252	87%	4,978	53.63	6946
		24.5	7	70	80	APC E	20 x 10	252	87%	5,226	42.61	5698
		21	6	70	80	APC E	22 x 10	252	87%	4,414	42.47	5380
		21	6	70	80	APC E	20 x 10	252	87%	4,602	33.46	4420
		28	8	70	80	APC E	20 x 10	260	86%	5,898	54.67	7259
		28	8	70	80	APC E	17 x 10	260	86%	6,342	36.41	4686
		31.5	9	70	80	APC E	17 x 8	260	91%	7,368	36.26	5832

JP Number	Name	Voltage	LiXx Cells	Max Load (5min)	Max Load (60 sec)	Propeller	Dia. x Pitch	kV	Efficiency	RPM	Load Current	Thrust (g)
		31.5	9	70	80	APC E	17 x 10	260	91%	7,158	44.8	5969