

Page 1/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.09.2023 Version number: 1.07 Revision: 18.09.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier For Industrial and Professional use only.
- · Trade name: Guild Lane Banana Oil
- · Article number: 110
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against Surface Coating
- · Application of the substance / the mixture

Surface Coating

Surface Coating Additive

- · 1.3 Details of the supplier of the safety data sheet
- · Supplier:

J PERKINS (DISTRIBUTION) LIMITED

Northdown Business Park,

Ashford Road,

Lenham,

Maidstone.

ME17 2DL

UNITED KINGDOM

TEL: +44 (0)1622 854 300

EMAIL: sales@jperkins.com

- · Further information obtainable from: sales@jperkins.com
- · 1.4 Emergency telephone number: +44 (0)1622 854 300 (business hours)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated

exposure.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms







GHS02

GHS07

GHS08

(Contd. of page 1)

Safety data sheet according to 1907/2006/EC, Article 31

Version number: 1.07 Printing date 18.09.2023 Revision: 18.09.2023

Trade name: Guild Lane Banana Oil

· Signal word Danger

· Hazard-determining components of labelling:

Xylene (mix)

Butyl ethanoate

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P241 *Use explosion-proof [electrical/ventilating/lighting] equipment.*

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-XXXX	Butyl ethanoate Flam. Liq. 3, H226; STOT SE 3, H336	>25- ≤ 50%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	Xylene (mix) ♠ Flam. Liq. 3, H226; ♣ STOT RE 2, H373; Asp. Tox. 1, H304; ♠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	>25-≤50%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25-XXXX	propan-2-ol	>10-≤25%
EINECS: 200-662-2	propan-2-one	>2.5- ≤ 10%
EINECS: 202-849-4	ethylbenzene	>2.5- ≤ 10%

Printing date 18.09.2023 Version number: 1.07 Revision: 18.09.2023

Trade name: Guild Lane Banana Oil

		Contd. of page 2)
CAS: 9004-70-0	Nitrocellulose (12.3% N)	>2.5- ≤ 10%
EC number: 682-719-5	♦ Expl. 1.1, H201	
CAS: 78-83-1	isobutanol	>1- ≤ 2.5%
EINECS: 201-148-0 Reg.nr.: 01-2119484609-23-XXXX	♦ Flam. Liq. 3, H226; ♦ Eye Dam. 1, H318; ♦ Skin Irrit. 2, H315; STOT SE 3, H335-H336	
CAS: 28553-12-0	di-iso nonyl phthalate	>1- ≤ 2.5%
EINECS: 249-079-5	substance with a Community workplace exposure limit	
Reg.nr.: 01-2119430798-28-xxxx		

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing. Immediately rinse with water.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately and show safety datasheet or label.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

(Contd. on page 4)

Printing date 18.09.2023 Version number: 1.07 Revision: 18.09.2023

Trade name: Guild Lane Banana Oil

(Contd. of page 3)

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Ensure good ventilation/extraction at the workplace.

Prevent formation of aerosols.

Hygiene measures:

Wash hands before breaks and at the end of workday.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed and in a well-ventilated place.

Keep away from heat.

Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with	limit values that red	quire monitoring at t	he workplace:
--------------------	-----------------------	-----------------------	---------------

123-86-4 Butyl ethanoate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

1330-20-7 Xylene (mix)

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV 67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm

67-64-1 propan-2-one

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

100-41-4 ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm

(Contd. on page 5)

 Printing date 18.09.2023
 Version number: 1.07
 Revision: 18.09.2023

Trade name: Guild Lane Banana Oil

78-83-1 is	hutan	(Contd.	of p
		value: 231 mg/m³, 75 ppm	
		value: 154 mg/m³, 50 ppm	
		nonyl phthalate	
		value: 5 mg/m³	
DNELs	,		
123-86-4 I	Butyl eti	hanoate	
Oral		2 mg/day (Con)	
Dermal		6 mg/day (Con)	
Bermai	DIVE	11 mg/day (Ind)	
Inhalative	DNEL	$35.7 \text{ mg/m}^3 \text{ (Con)}$	
11111111111111	DIVE	300 mg/m³ (Ind)	
1330-20-7	Xvlene		
Dermal	•	108 mg/day (Con)	
		180 mg/day (Ind)	
Inhalative	DNEL	$14.8 \text{ mg/m}^3 (Con)$	
		$77 \text{ mg/m}^3 (Ind)$	
67-63-0 pr	opan-2		
Oral	-	26 mg/day (Con)	
Dermal	DNEL	319 mg/day (Con)	
		888 mg/day (Ind)	
Inhalative	DNEL	$89 \text{ mg/m}^3 (Con)$	
		$500 \text{ mg/m}^3 (Ind)$	
67-64-1 pr	opan-2	-one	
Oral	DNEL	62 mg/day (Con)	
Dermal	DNEL	62 mg/day (Con)	
		186 mg/day (Ind)	
Inhalative	DNEL	$200 \text{ mg/m}^3 \text{ (Con)}$	
		1,210 mg/m³ (Ind)	
78-83-1 is	butana	ol	
Oral	DNEL	25 mg/day (Con)	
		55 mg/m³ (Con)	
		$310 \text{ mg/m}^3 \text{ (Ind)}$	
28553-12-	0 di-iso	nonyl phthalate	
Oral	DNEL	4.4 mg/day (Con)	
Dermal	DNEL	220 mg/day (Con)	
		366 mg/day (Wor)	
Inhalative	DNEL	$15.3 \text{ mg/m}^3 (Con)$	
		51.72 mg/m³ (Wor)	

CAS No. 1330-20-7 Xylene mixed isomers

- Fresh water; 0.327 mg/l
- Marine water; 0.327 mg/l
- Intermittent release; $0.327 \ mg/l$
- STP; 6.58 mg/l

(Contd. on page 6)

Printing date 18.09.2023 Version number: 1.07 Revision: 18.09.2023

Trade name: Guild Lane Banana Oil

(Contd. of page 5)

- Sediment (Freshwater); 12.46 mg/kg - Sediment (Marinewater); 12.46 mg/kg

- Soil; 2.31 mg/kg

CAS No. 123-86-4 Butyl Acetate

Freshwater: 0.18 mg/l Marine water: 0.018 mg/l

Fresh water sediment: 0.981 mg/kg Marine sediment: 0.0981 mg/kg

Soil: 0.0903 mg/kg

STP (sewage-treatment plant): 35.6 mg/l Intermittent use/release: 0.36 mg/l

· Ingredients with biological limit values:

1330-20-7 Xylene (mix)

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

 ${\it Store protective clothing separately}.$

Avoid contact with the eyes and skin.

- · Respiratory protection: When spraying the product, use a respiratory protective device.
- · Protection of hands:

When skin exposure may occur, advice should be sought from the glove supplier on appropriate types and usage times for this product.



Protective gloves

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid Colour: Clear

• Odour: Characteristic
• Odour threshold: Not determined.

(Contd. on page 7)

Printing date 18.09.2023 Version number: 1.07 Revision: 18.09.2023

Trade name: Guild Lane Banana Oil

	(Contd. of page
pH-value:	Not determined.
Change in condition Melting point/freezing point: Initial boiling point and boiling range	Undetermined. :: 55.8°C
Flash point:	-17 °C
Flammability (solid, gas):	Highly flammable.
Ignition temperature:	415 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
Explosion limits: Lower: Upper:	1.1 Vol % 12 Vol %
· Vapour pressure at 20 °C:	60.2 hPa
Density at 20°C: Relative density Vapour density Evaporation rate	0.873 g/cm³ Not determined. Not determined. Not determined.
· Solubility in / Miscibility with water:	NOT MISCIBLE
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic: Kinematic at 20°C:	Not determined. 18 s (DIN 53211/4)
Solvent content: Organic solvents:	95.5 %
Solids content:	4.5 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

No dangerous decomposition products when stored and handled correctly

Printing date 18.09.2023 Version number: 1.07 Revision: 18.09.2023

Trade name: Guild Lane Banana Oil

(Contd. of page 7)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

122.07.43		vant for classification:
123-86-4 I		
Oral	LD50	10,760 mg/kg (rat)
Dermal	LD50	14,112 mg/kg (Rab)
Inhalative	LC50/4 h	23.4 mg/l (Rat)
<i>1330-20-7</i>	Xylene (m	ix)
Oral	LD50	5,000 mg/kg (Rat)
Dermal	<i>LD50</i>	2,000 mg/kg (rbt)
Inhalative	LC50/4 h	11 mg/l (Rat)
67-63-0 pr	opan-2-ol	
Oral	LD50	5,840 mg/kg (Rat)
Dermal	LD50	13,900 mg/kg (Rab)
Inhalative	LC50/4 h	>25 mg/l (Rat)
67-64-1 pr	opan-2-on	e
Oral	LD50	5,800 mg/kg (Rat)
Dermal	LD50	7,400 mg/kg (Rabbit)
Inhalative	LC50/4 h	76 mg/l (Rat)
100-41-4 е	thylbenzer	ne e
Oral	LD50	3,500 mg/kg (rat)
Dermal	<i>LD50</i>	17,800 mg/kg (rbt)
9004-70-0	Nitrocellu	lose (12.3% N)
Oral	LD50	>5,000 mg/kg (Rat)
78-83-1 is	obutanol	
Oral	LD50	>2,000 mg/kg (Rat)
Dermal	<i>LD50</i>	>2,000 mg/kg (Rab)
28553-12-	0 di-iso no	nyl phthalate
Oral	LD50	>10,000 mg/kg (Rat)
Dermal	LD50	>3,160 mg/kg (Rabbit)
Inhalatina	I C50/1 h	>4.4 mg/l (Rat)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

(Contd. on page 9)

Printing date 18.09.2023 Version number: 1.07 Revision: 18.09.2023

Trade name: Guild Lane Banana Oil

(Contd. of page 8)

· STOT-repeated exposure

May cause damage to the hearing organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

Acute Fish toxicity n-Butyl acetate

LC50 18 mg/l

Species: Pimephales promelas (fathead minnow)

Exposure duration: 96 h

Chronic Fish toxicity n-Butyl acetate
No data available.

Acute toxicity for daphnia

n-Butyl acetate EC50 44 mg/l

Species: Daphnia (water flea) Exposure duration: 48 h

Chronic toxicity to daphnia

n-Butyl acetate NOEC 23 mg/l

Species: Daphnia magna (Water flea)

Exposure duration: 21 d

Method: OECD Test Guideline 211

Acute toxicity for algae

n-Butyl acetate EC50 675 mg/l

Species: Scenedesmus quadricauda (Green algae)

Exposure duration: 72 h

Acute bacterial toxicity

EC50 356 mg/l

Species: activated sludge Exposure duration: 40 h

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

The Continuing water if even small quantities team int

Harmful to aquatic organisms

(Contd. on page 10)

Printing date 18.09.2023 Version number: 1.07 Revision: 18.09.2023

Trade name: Guild Lane Banana Oil

(Contd. of page 9)

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	
· 14.1 UN-Number · ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name · ADR	1263 PAINT RELATED MATERIAL (vapour pressure at 50° not more than 110 kPa)
· IMDG, IATA	PAINT RELATED MATERIAL
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group · ADR, IMDG, IATA	II
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	33
· EMS Number:	F-E, <u>S-E</u> B
Stowage Category	
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	f Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	<i>5L</i>
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
· Transport category	Maximum net quantity per outer packaging: 500 ml 2
Transport category	

Printing date 18.09.2023 Version number: 1.07 Revision: 18.09.2023

Trade name: Guild Lane Banana Oil

	(Contd. of page 10
· Tunnel restriction code	D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL (VAPOUR PRESSURE AT 50°C NOT MORE THAN 110 KPA), 3, II

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	95.5

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Full text of H-Statements referred to under sections 2 and 3:

H201 Explosive; mass explosion hazard.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

- · Department issuing SDS: Product safety department: LABORATORY
- · Contact: Health & Safety Officer
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 12)

Printing date 18.09.2023 Version number: 1.07 Revision: 18.09.2023

Trade name: Guild Lane Banana Oil

(Contd. of page 11)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Expl. 1.1: Explosives – Division 1.1

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.

GB