

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.09.2018

Revision: 01.06.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

For professional use only

- **1.1 Product identifier** For professional use only
- **Trade name: *Chroma Fuel-Proof Enamel Paint, Aerosol***
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** Surface Coating
- **Application of the substance / the mixture**
Surface Coating
Surface Coating
Synthetic Topcoat
- **1.3 Details of the supplier of the safety data sheet**
- **Supplier:**
J PERKINS DISTRIBUTION LTD.
NORTHDOWN CLOSE, ASHFORD ROAD
LENHAM, KENT. ME17 2DL
UNITED KINGDOM
TEL: +44 (0)1622 854 300
EMAIL: sales@jperkins.com
- **Further information obtainable from:** sales@jperkins.com
- **1.4 Emergency telephone number:** +44 (0)1622 854 300 (Business hours)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

Aerosol 1	H222-H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
STOT RE 1	H372	Causes damage to organs through prolonged or repeated exposure.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS08

- **Signal word** Danger
- **Hazard-determining components of labelling:**
Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics
- **Hazard statements**
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H372 Causes damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.
H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.09.2018

Revision: 01.06.2018

Trade name: Chroma Fuel-Proof Enamel Paint, Aerosol

(Contd. of page 1)

- P331 Do NOT induce vomiting.
 P405 Store locked up.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

Buildup of explosive mixtures possible without sufficient ventilation.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37	dimethyl ether ⚠ Flam. Gas 1, H220; Press. Gas C, H280	50-100%
EC number: 919-446-0 Reg.nr.: 01-2119458049-33-xxxx	Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 1, H372; Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H336	2.5-10%
EC number: 927-344-2	H y d r o c a r b o n s , C 9 - C 1 0 , n - alkanes, isoalkanes, cyclics, aromatics (2-25%) ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Acute Tox. 4, H302; STOT SE 3, H336	2.5-10%
CAS: 64742-48-9 EINECS: 265-150-3	Naphtha (petroleum), hydrotreated heavy ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ STOT SE 3, H336	2.5-10%
EC number: 919-446-0	Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 1, H372; Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H336	2.5-10%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35-xxxx	Solvent naphtha (petroleum), light arom. ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Acute Tox. 4, H332; STOT SE 3, H335-H336	≤ 2.5%
CAS: 108-88-3 EINECS: 203-625-9 Reg.nr.: 01-2119471310-51-xxxx	Toluene ⚠ Flam. Liq. 2, H225; ⚠ Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336; Aquatic Chronic 3, H412	≤ 2.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:**

Do not induce vomiting; call for medical help immediately and show safety datasheet or label.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.09.2018

Revision: 01.06.2018

Trade name: Chroma Fuel-Proof Enamel Paint, Aerosol

(Contd. of page 2)

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/extraction at the workplace.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Keep respiratory protective device available.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risk of fires, all contaminated materials should be [stored in purpose-built containers or in metal containers with tight-fitting self-closing lids.] or [laid out flat in a single layer to dry] or [placed in a metal container soaked with water] or [washed out well with warm soapy water before disposal.] Contaminated materials should be removed from the workplace at the end of each working day and stored outside.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed and in a well-ventilated place.
Keep away from heat.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 11.09.2018

Revision: 01.06.2018

Trade name: **Chroma Fuel-Proof Enamel Paint, Aerosol**

(Contd. of page 3)

· 7.3 **Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.· 8.1 **Control parameters**· **Ingredients with limit values that require monitoring at the workplace:****115-10-6 dimethyl ether**

WEL	Short-term value: 958 mg/m ³ , 500 ppm
	Long-term value: 766 mg/m ³ , 400 ppm

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics

WEL	Long-term value: 350 mg/m ³
-----	--

Solvent naphtha (petroleum), light arom.

OEL	Long-term value: 100 mg/m ³
-----	--

108-88-3 Toluene

WEL	Short-term value: 384 mg/m ³ , 100 ppm
	Long-term value: 191 mg/m ³ , 50 ppm
	Sk

· **DNELs****115-10-6 dimethyl ether**

Inhalative	DNEL	471 mg/m ³ (Con)
		1,894 mg/m ³ (Ind)

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics

Oral	DNEL	26 mg/day (Con)
Dermal	DNEL	26 mg/day (Con)
		44 mg/day (Ind)
Inhalative	DNEL	71 mg/m ³ (Con)
		330 mg/m ³ (Ind)

Solvent naphtha (petroleum), light arom.

Oral	DNEL	11 mg/day (Con)
Dermal	DNEL	11 mg/day (Con)
		25 mg/day (Ind)
Inhalative	DNEL	32 mg/m ³ (Con)
		150 mg/m ³ (Ind)

108-88-3 Toluene

Oral	DNEL	8.13 mg/day (Con)
Dermal	DNEL	226 mg/day (Con)
		384 mg/day (Ind)
Inhalative	DNEL	56.5 mg/m ³ (Con)
		192 mg/m ³ (Ind)

· **PNECs**

CAS No. 1330-20-7 Xylene mixed isomers

- Fresh water; 0.327 mg/l
- Marine water; 0.327 mg/l
- Intermittent release; 0.327 mg/l
- STP; 6.58 mg/l
- Sediment (Freshwater); 12.46 mg/kg
- Sediment (Marinewater); 12.46 mg/kg
- Soil; 2.31 mg/kg

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.09.2018

Revision: 01.06.2018

Trade name: Chroma Fuel-Proof Enamel Paint, Aerosol

(Contd. of page 4)

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
- **Respiratory protection:** When spraying the product, use a respiratory protective device.
- **Protection of hands:**
When skin exposure may occur, advice should be sought from the glove supplier on appropriate types and usage times for this product.



Protective gloves

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**
Safety glasses



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	Aerosol
Colour:	According to product specification
- **Odour:** Characteristic
- **Odour threshold:** Not determined.
- **pH-value:** Not determined.
- **Change in condition**

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	-24.9 °C
- **Flash point:** -42 °C
- **Flammability (solid, gas):** Not applicable.
- **Ignition temperature:** >200 °C
- **Decomposition temperature:** Not determined.
- **Auto-ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Heating may cause an explosion.
- **Explosion limits:**

Lower:	3.0 Vol %
---------------	-----------

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 11.09.2018

Revision: 01.06.2018

Trade name: Chroma Fuel-Proof Enamel Paint, Aerosol

(Contd. of page 5)

Upper:	18.6 Vol %
· Vapour pressure at 20 °C:	5200 hPa
· Density at 20 °C:	0.785 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water:	NOT MISCIBLE
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	72.8 %
Solids content:	21.2 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
No dangerous decomposition products when stored and handled correctly

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

115-10-6 dimethyl ether

Inhalative	LC50/4 h	164,000 mg/l (rat)
------------	----------	--------------------

Hydrocarbons, C9-I2, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics

Oral	LD50	>15,000 mg/kg (Rat)
Dermal	LD50	>3,400 mg/kg (Rab)
Inhalative	LC50/4 h	13.1 mg/l (Rat)

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Oral	LD50	>1,500 mg/kg (Rat)
Dermal	LD50	>4,200 mg/kg (Rat)
Inhalative	LC50/4 h	>13.1 mg/l (Rat)

64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral	LD50	>15,000 mg/kg (Rat)
Dermal	LD50	>3,000 mg/kg (Rab)
Inhalative	LC50/4 h	>6.1 mg/l (Rat)

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 11.09.2018

Revision: 01.06.2018

Trade name: Chroma Fuel-Proof Enamel Paint, Aerosol

(Contd. of page 6)

Solvent naphtha (petroleum), light arom.

Oral	LD50	3,492 mg/kg (rat)
Dermal	LD50	3,160 mg/kg (Rab)
Inhalative	LC50/4 h	6,193 mg/l (rat)

108-88-3 Toluene

Oral	LD50	5,580 mg/kg (Rat)
Dermal	LD50	5,000 mg/kg (Rab)
Inhalative	LC50/4 h	20 mg/l (Rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure**
Causes damage to organs through prolonged or repeated exposure.
- **Aspiration hazard**
May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:**
- Acute Fish toxicity
Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)
LC50 9.22 mg/l
Species: *Oncorhynchus mykiss* (rainbow trout)
Exposure duration: 96 h
- Acute toxicity for daphnia
Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)
EC50 6.14 mg/l
Species: *Daphnia magna* (Water flea)
Exposure duration: 48 h
- Acute toxicity for algae
Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)
ErC50 2.9 mg/l
Species: *Pseudokirchneriella subcapitata* (green algae)
Exposure duration: 72 h
- Acute bacterial toxicity
Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)
EC50 1 - 10 mg/l
- Ecotoxicology Assessment
Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)
Chronic aquatic toxicity: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Data based on the safety data sheet (SDS) by the supplier.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 11.09.2018

Revision: 01.06.2018

Trade name: **Chroma Fuel-Proof Enamel Paint, Aerosol**



(Contd. of page 7)

- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|---|--|
| <ul style="list-style-type: none"> · 14.1 UN-Number · ADR, IMDG, IATA | UN1950 |
| <ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG · IATA | 1950 AEROSOLS
AEROSOLS
AEROSOLS, flammable |
| <ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR | <div style="text-align: center;">  </div> |
| <ul style="list-style-type: none"> · Class · Label | 2 5F Gases.
2.1 |
| <ul style="list-style-type: none"> · IMDG, IATA | <div style="text-align: center;">  </div> |
| <ul style="list-style-type: none"> · Class · Label | 2.1
2.1 |
| <ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA | Void |
| <ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: | no |
| <ul style="list-style-type: none"> · 14.6 Special precautions for user · Danger code (Kemler): | Warning: Gases.
- |

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 11.09.2018

Revision: 01.06.2018

Trade name: **Chroma Fuel-Proof Enamel Paint, Aerosol**

(Contd. of page 8)

· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	120 ml
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	1
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
 - **Directive 2012/18/EU**
 - **Named dangerous substances - ANNEX I** None of the ingredients is listed.
 - **Seveso category P3a FLAMMABLE AEROSOLS**
 - **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
 - **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
 - **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
 - **National regulations:**
 - **Technical instructions (air):**
- | Class | Share in % |
|-------|------------|
| I | 0.1 |
| NK | 72.8 |
- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
 - **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Full text of H-Statements referred to under sections 2 and 3:**
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 11.09.2018

Revision: 01.06.2018

Trade name: Chroma Fuel-Proof Enamel Paint, Aerosol

(Contd. of page 9)

H226 *Flammable liquid and vapour.*
 H280 *Contains gas under pressure; may explode if heated.*
 H302 *Harmful if swallowed.*
 H304 *May be fatal if swallowed and enters airways.*
 H315 *Causes skin irritation.*
 H332 *Harmful if inhaled.*
 H335 *May cause respiratory irritation.*
 H336 *May cause drowsiness or dizziness.*
 H361d *Suspected of damaging the unborn child.*
 H372 *Causes damage to organs through prolonged or repeated exposure.*
 H373 *May cause damage to organs through prolonged or repeated exposure.*
 H411 *Toxic to aquatic life with long lasting effects.*
 H412 *Harmful to aquatic life with long lasting effects.*

· **Department issuing SDS:** Product safety department: LABORATORY

· **Contact:** Health & Safety Officer

· **Abbreviations and acronyms:**

RID: *Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*

ICAO: *International Civil Aviation Organisation*

ADR: *Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

IMDG: *International Maritime Code for Dangerous Goods*

IATA: *International Air Transport Association*

GHS: *Globally Harmonised System of Classification and Labelling of Chemicals*

EINECS: *European Inventory of Existing Commercial Chemical Substances*

ELINCS: *European List of Notified Chemical Substances*

CAS: *Chemical Abstracts Service (division of the American Chemical Society)*

DNEL: *Derived No-Effect Level (REACH)*

PNEC: *Predicted No-Effect Concentration (REACH)*

LC50: *Lethal concentration, 50 percent*

LD50: *Lethal dose, 50 percent*

PBT: *Persistent, Bioaccumulative and Toxic*

vPvB: *very Persistent and very Bioaccumulative*

Flam. Gas 1: *Flammable gases – Category 1*

Aerosol 1: *Aerosols – Category 1*

Press. Gas C: *Gases under pressure – Compressed gas*

Flam. Liq. 2: *Flammable liquids – Category 2*

Flam. Liq. 3: *Flammable liquids – Category 3*

Acute Tox. 4: *Acute toxicity – Category 4*

Skin Irrit. 2: *Skin corrosion/irritation – Category 2*

Repr. 2: *Reproductive toxicity – Category 2*

STOT SE 3: *Specific target organ toxicity (single exposure) – Category 3*

STOT RE 1: *Specific target organ toxicity (repeated exposure) – Category 1*

STOT RE 2: *Specific target organ toxicity (repeated exposure) – Category 2*

Asp. Tox. 1: *Aspiration hazard – Category 1*

Aquatic Chronic 2: *Hazardous to the aquatic environment - long-term aquatic hazard – Category 2*

Aquatic Chronic 3: *Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*