# LANITZ-PRENA FOLIEN FACTORY GMBH

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

# **Oracover® SOLVENT (THINNER)**

Revision date: 08.01.2019

Page 1 of 9

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

# 1.1. Product identifier

Oracover® SOLVENT (THINNER)

REACH Registration Number:	01-2119457290-43-
CAS No:	78-93-3
Index No:	606-002-00-3
EC No:	201-159-0

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

# Use of the substance/mixture

Solvent/Thinner.

# 1.3. Details of the supplier of the safety data sheet

Company name:	Lanitz Prena Folien Factory GmbH	
Street:	Am Ritterschlösschen 20	
Place:	04179 Leipzig	
Contact person:	Frau Ploss / Albrecht	Telephone: +49 - 341 - 44 23 05 - 34
e-mail:	labor@oracover.de	
1.4. Emergency telephone	+49 (0)6132-84463 (24 h)	
number:		

# SECTION 2: Hazards identification

# 2.1. Classification of the substance or mixture

#### Regulation (EC) No. 1272/2008

Hazard categories: Flammable liquid: Flam. Liq. 2 Serious eye damage/eye irritation: Eye Irrit. 2 Specific target organ toxicity - single exposure: STOT SE 3 Hazard Statements: Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness.

# 2.2. Label elements

# Regulation (EC) No. 1272/2008

Signal word:	Danger
olgilal nota:	Danger

#### **Pictograms:**



#### **Hazard statements**

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

# Precautionary statements

recautionary statemen	ts
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 P305+P351+P338	Avoid breathing dust/fume/gas/mist/vapours/spray. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

Page 2 of 9

# LANITZ-PRENA FOLIEN FACTORY GMBH

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

# **Oracover® SOLVENT (THINNER)**

Revision date: 08.01.2019

	present and easy to do. Continue rinsing.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of waste according to applicable legislation.

#### Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

#### 2.3. Other hazards

This substance does not meet the criteria for classification as PBT or vPvB.

#### **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

#### Hazardous components

CAS No	Chemical name			Quantity	
	EC No	Index No	REACH No		
	GHS Classification				
78-93-3	butanone; ethyl methyl ketone			80-100 %	
	201-159-0 606-002-00-3 01-2119457290-43-				
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066				

Full text of H and EUH statements: see section 16.

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### **General information**

Move victim out of danger zone. Remove contaminated, saturated clothing immediately. Get medical advice/attention if you feel unwell. If unconscious place in recovery position and seek medical advice. Self-protection of the first aider

#### After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration.

#### After contact with skin

Wash with plenty of soap and water.

#### After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing.

#### After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Call a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

Narcotic effects. Respiratory complaints. Headache. Dizziness.

# 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Subsequent observance for pneumonia and lung oedema. To supervise the blood circulation.

# **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

#### Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings. (Water spray jet, alcohol resistant foam, BC-powder, Carbon dioxide (CO2) )

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

#### **Oracover® SOLVENT (THINNER)**

Revision date: 08.01.2019

Page 3 of 9

#### Unsuitable extinguishing media

Full water jet

# 5.2. Special hazards arising from the substance or mixture

In use may form flammable/explosive vapour-air mixture. The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration. Formation of: Carbon monoxide. Carbon dioxide (CO2).

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

#### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protection equipment. Remove persons to safety. In case of insufficient ventilation, wear suitable respiratory equipment.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

#### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Cover drains.

#### 6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

Provide adequate ventilation as well as local exhaustion at critical locations. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours can form explosive mixtures with air.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Use only outdoors or in a well-ventilated area. Ground and bond container and receiving equipment. Use explosion-proof machinery, apparatus, ventilation facilities, tools etc. Use only antistatically equipped (spark-free) tools.

#### Further information on handling

Wash hands thoroughly after handling.

#### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Provide adequate ventilation.

#### Hints on joint storage

Keep away from food, drink and animal feedingstuffs. Protect against direct sunlight.

#### 7.3. Specific end use(s)

Solvent/Thinner.

#### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

# **Oracover® SOLVENT (THINNER)**

Revision date: 08.01.2019

Page 4 of 9

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL

#### **Biological Monitoring Guidance Values (EH40)**

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

#### **DNEL/DMEL** values

CAS No	Substance				
DNEL type		Exposure route	Effect	Value	
78-93-3	butanone; ethyl methyl ketone				
Worker DNEL,	long-term	inhalation	systemic	600 mg/m³	
Worker DNEL,	long-term	dermal	•	1161 mg/kg bw/day	

### **PNEC** values

CAS No	Substance		
Environmen	tal compartment	Value	
78-93-3	butanone; ethyl methyl ketone		
Freshwater		55,8 mg/l	
Marine wate	farine water 55,8 mg/l		
Freshwater sediment 284,74 mg/kg		284,74 mg/kg	
Marine sediment 284,7 mg/		284,7 mg/kg	
Secondary poisoning		1000 mg/kg	
Micro-organisms in sewage treatment plants (STP)		709 mg/l	
Soil		22,5 mg/kg	

#### 8.2. Exposure controls





Appropriate engineering controls Provide adequate ventilation.

# Protective and hygiene measures

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink. Protect skin by using skin protective cream.

#### Eye/face protection

Wear eye protection/face protection.

#### Hand protection

Wear suitable gloves. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned

# LANITZ-PRENA FOLIEN FACTORY CMBH

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

# **Oracover® SOLVENT (THINNER)**

Revision date: 08.01.2019

above together with the supplier of these gloves. (EN 374)

# Skin protection

Wear suitable protective clothing.

# **Respiratory protection**

In case of inadequate ventilation wear respiratory protection.

#### Environmental exposure controls

Do not allow to enter into surface water or drains.

#### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	characteristic	
pH-Value:		not determined
Changes in the physical state		
Melting point:		-86 °C
Initial boiling point and boiling range	e:	79,5 °C
Sublimation point:		not determined
Softening point:		not determined
Pour point:		not determined
Flash point:		-9 °C
Flammability		
Solid:		not applicable
Gas:		not applicable
Explosive properties		
Vapours can form explosive mix	ctures with air.	
Lower explosion limits:		1,5 vol. %
Upper explosion limits:		11,5 vol. %
Ignition temperature:		404 °C
Auto-ignition temperature		
Solid:		not applicable
Gas:		not applicable
Decomposition temperature:		not determined
Oxidizing properties		
Not oxidising.		
Vapour pressure:		126 hPa
(at 25 °C)		/
Density (at 20 °C):		0,805 g/cm³
Water solubility:		250 g/L
(at 20 °C) Solubility in other solvents		
not determined		
Partition coefficient:		0.3
Viscosity / dynamic:		not determined
Viscosity / kinematic:		not determined
Flow time:		(4 mm) 11 s

# LANITZ-PRENA FOLIEN FACTORY GMBH

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

----

Revision date: 08.01.2019		Page 6 of 9
Vapour density:	not determined	
Evaporation rate:	not determined	
9.2. Other information		
Solid content:	0 %	
Odour threshold: not determined Temperature class T2 Surface tension 24,8 mN/m (20°C)		
CECTION 40. Stability and reactivity		

# SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Ignition hazard.

# 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

#### 10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### 10.5. Incompatible materials

Oxidizing agents.

#### 10.6. Hazardous decomposition products

In case of fire: Carbon monoxide. Carbon dioxide (CO2).

#### **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

# Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

# STOT-single exposure

May cause drowsiness or dizziness. (butanone; ethyl methyl ketone)

# STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

# **SECTION 12: Ecological information**

# 12.1. Toxicity

The product is not: Ecotoxic.

# 12.2. Persistence and degradability

Readily biodegradable (according to OECD criteria).



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# **Oracover® SOLVENT (THINNER)**

Revision date: 08.01.2019

Page 7 of 9

CAS No	Chemical name				
	Method	Value		d	Source
	Evaluation	•			
78-93-3	butanone; ethyl methyl ketone				
		98 %			OECD 301D/ EEC 92/69/V, C.4-E
	Readily biodegradable (according to OECD criteria).				•

#### 12.3. Bioaccumulative potential

The product has not been tested.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
78-93-3	butanone; ethyl methyl ketone	0,3

#### 12.4. Mobility in soil

No information available.

### 12.5. Results of PBT and vPvB assessment

This substance does not meet the criteria for classification as PBT or vPvB.

#### 12.6. Other adverse effects

No information available.

#### **Further information**

Avoid release to the environment.

#### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

# Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

#### Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

# **SECTION 14: Transport information**

Land transport (ADR/RID)	
<u>14.1. UN number:</u>	UN 1193
14.2. UN proper shipping name:	ETHYL METHYL KETONE (METHYL ETHYLKETONE)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Classification code:	F1
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E
Inland waterways transport (ADN)	
<u>14.1. UN number:</u>	UN 1193

# LANITZ-PRENA FOLIEN FACTORY GMBH

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

	according to Regulation (EC) No 1907/2008	
	Oracover® SOLVENT (THINNER)	
Revision date: 08.01.2019		Page 8 of 9
14.2. UN proper shipping name:	ETHYL METHYL KETONE (METHYL ETHYLKETONE)	
14.3. Transport hazard class(es):	3	
14.4. Packing group:	II	
Hazard label:	3	
	3	
Classification code:	F1	
Limited quantity:	1L	
Excepted quantity:	E2	
Marine transport (IMDG)	UN 1193	
<u>14.1. UN number:</u> 14.2. UN proper shipping name:	ETHYL METHYL KETONE (METHYL ETHYLKETONE)	
14.2. ON proper snipping name. 14.3. Transport hazard class(es):	3	
14.4. Packing group:	5 	
Hazard label:	3	
Special Provisions:	- <b>*</b>	
Limited quantity:	1 L	
Excepted quantity:	E2	
EmS:	F-E, S-D	
Air transport (ICAO-TI/IATA-DGR)		
14.1. UN number:	UN 1193	
14.2. UN proper shipping name:	ETHYL METHYL KETONE	
14.3. Transport hazard class(es):	3	
14.4. Packing group:		
Hazard label:	3	
Limited quantity Passenger:	3 1 L	
Passenger LQ:	Y341	
Excepted quantity:	E2	
IATA-packing instructions - Passenger:	353	
IATA-max. quantity - Passenger:	5 L	
IATA-packing instructions - Cargo:	364	
IATA-max. quantity - Cargo:	60 L	
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	no	
14.6. Special precautions for user No information available.		
14.7. Transport in bulk according to Annex	II of Marnol and the IBC Code	
not applicable		
SECTION 15: Populatory information		

# **SECTION 15: Regulatory information**

# LANITZ-PRENA FOLIEN FACTORY CmbH

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

### **Oracover® SOLVENT (THINNER)**

Revision date: 08.01.2019

Page 9 of 9

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information	
Restrictions on use (REACH, annex XVII	():
Entry 3: butanone; ethyl methyl ketor	1e
2010/75/EU (VOC):	100 %
2004/42/EC (VOC):	100 %
Information according to 2012/18/EU (SEVESO III):	P5c FLAMMABLE LIQUIDS
National regulatory information	
Employment restrictions:	Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).
Water contaminating class (D):	1 - slightly water contaminating
15.2. Chemical safety assessment	

Chemical safety assessments for substances in this mixture were not carried out.

#### **SECTION 16: Other information**

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service LC50: Lethal concentration, 50% LD50: Lethal dose, 50% Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

#### **Further Information**

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singulary responsible for adhering to existing laws and regulations.